

PAGE NO.	Dimension(m m)	Parts Number	Polar Pattern		Connection type			Standard testing condition	Sensitivity (dB)
			Omnidirectional	Unidirectional	SMD	Soldering Type	Pin Type		
1	φ3.0×1.2	TSS-3012E	◎		◎			2.0V,2.2KΩ	-39 ~ -49
2	φ4.0×1.3	TSS-4012E	◎		◎			2.0V,2.2KΩ	-39 ~ -49
3	φ3.0×1.5	TSB-3015A	◎			◎		2.0V,2.2KΩ	-39 ~ -49
4	φ4.0×1.5	TSB-4015A/ BP	◎			◎	◎	2.0V,2.2KΩ	-33 ~ -49
5	φ6.0×1.8	TSB-6018A	◎			◎		2.0V,2.2KΩ	-29 ~ -47
6	φ6.0×2.2	TSB-6022A/ BP	◎			◎	◎	2.0V,2.2KΩ	-29 ~ -47
7	φ6.0×2.7	TSB-6027A/ BP	◎			◎	◎	2.0V,2.2KΩ	-29 ~ -47
8	φ9.7×4.5	TSB-9745A/BP	◎			◎	◎	2.0V,2.2KΩ	-27 ~ -49
9	φ12×14.3	TSB-120A31O	◎			◎		1.5V,2.2KΩ	-42 ~ -48