

RIGID & IMC Conduit Fittings


Polyethylene



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
95210	1/2"	100	1000	1
95220	3/4"	100	1000	1
95230	1"	50	500	2
95240	1-1/4"	25	250	3
95250	1-1/2"	25	250	3
95260	2"	20	200	6
95265	2-1/2"	-	25	11
95270	3"	-	25	14
95275	3-1/2"	-	25	22
95280	4"	-	25	23
95285	5"	-	10	28
95290	6"	-	10	34

NOMINAL DIMENSIONS (Inches):

Part No	A	B
95210	1.050	0.360
95220	1.290	0.400
95230	1.630	0.490
95240	1.930	0.480
95250	2.180	0.480
95260	2.640	0.540
95265	3.250	0.630
95270	3.900	0.680
95275	4.410	0.680
95280	4.930	0.680
95875	5.980	0.770
95290	7.060	0.770



Insulating Bushings Non-Metallic

MATERIAL: Polyethylene (Thermoplastic)
FINISH: Natural

APPLICATIONS:

- Used on threaded RIGID/IMC conduit to provide a rounded/smooth entrance to raceways
- Use with locknut to terminate threaded RIGID/IMC conduit to an outlet box

FEATURES:

- Made of high impact Polyethylene
- Rated at 105° C flame retardant

COMPLIANCE:



File No.:
E244047



Electrical Resource International
www.electrical-resource.com
440.978.1199