

NOTES:


- 1. THESE ARE FINISHED DIMENSIONS READY FOR THE LINER.
- 2. DIMENSIONS ARE FROM INSIDE POOL PANELS.
- ROPE AND FLOAT ASSEMBLY SHOULD BE INSTALLED IN ACCORDANCE WITH CURRENT ANSI/ASPS/ICC REGULATIONS
- HYDRA LINER TRACK FOR STEPS IS INSTALLED WITH THE BARB FACING THE RISER WALL ON THE STEP.

EXCAVATION NOTES:

- 5. ROUGH EXCAVATION SHOULD BE 2" DEEPER IN EACH INSTANCE.
- 6. SOIL TO HAVE MINIMUM BEARING CAPACITY OF 1500 PSF.
- 7. LOCATE TOP OF POOL AT LEAST 6" ABOVE THE SURROUNDING LAND ELEVATION.
- SEE "OVER DIG DETAIL" FOR EXCAVATION AROUND POOL.
- 9. FILL VOIDS UNDER BASE OF PANELS AND TAMP WELL.
- 10. BACK FILL WITH NON-EXPANSIVE MATERIAL.
- 11. FOLLOW ALL CURRENT ANSI / APSP / ICC GUIDELINES FOR RESIDENTIAL POOLS

IMPORTANT NOTES:

THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY. THE DEALER OR CONTRACTOR WHO SELLS OR INSTALLS YOUR POOL IS AN INDEPENDENT CONTRACTOR AND IS NOT AN AGENT OF THE MANUFACTURER. THE CONSTRUCTION METHODS ILLUSTRATED HERE ARE SUGGESTIONS AND APPLY ONLY TO NORMAL GROUND CONDITIONS. THERE MAY BE ADDITIONAL PRECAUTIONS AND/OR METHODS OF CONSTRUCTION. PROPER INSTALLATION IS THE RESPONSIBILITY OF THE DEALERBUILDER/CONTRACTOR.



ITEM	FILE NAME	DESCRIPTION	CUSTOMER DRAWING#	VENDOR PART #	QTY.
1	BOLT, PACK	BOLT, FLANGE, 3/8-16 X 1", PACK (50)	HPS1916	HPS1916	6
2	. ,	BRACE, STAMPED TRIANGLE, 52IN	HPSHTRIBRC	00025945	8
3	SIRAIGHI	PANEL, 4' LONG, 825 SERIES	HPSG104P	00027831	6
4	I KADIUS	PANEL, 6' RADIUS, 4' LONG, 825 SERIES	HPSG6R4	00027845	8
5	52 IN PANEL, RADIUS	PANEL, 6' RADIUS, FULL RADIUS FILL, 825 SERIES	HPSG6R21019	00027860	2
6	STAKE	STAKE, 14 GA	HPSSTAKE	00003484	8

	WEIGHT: lbs VOLUME:	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		10/10/2019	SAMSON STEEL			
άť	Inch ³	DECIMALS: X ±	DETAILED BY: bfoutz	DETAILED DATE:				
NUMBE	COLOR: HEAT TREAT:	XXX ± XXXX ±	LAST REVISED BY: bfoutz	10/29/2019	TITLE:	LAYOUT, 12X24 OVAL, 825 SERIES		
RAWING 87	FINISH:	ANGULAR: X ± 0.5	MATERIAL:					
79 79	TEXTURE:	THIRD ANGLE PROJECTION			PART NUMBER:		ISCALE: ISIZE:	
ENGINEERING DRAWING NUMBER: 00027987						00027987	1:100 SHEET: 1 OF 1	
w.	/working\000279	8 7	Į			0002:001	1011	