

Type	
Project	
Catalog No.	

*Measurement in inches



DESCRIPTION

Designed for new construction and retrofit applications this gimbaled square opening specification grade LED down light is available in 15W and 20W configuration. Incorporating the latest LED technology, the 15W light head produces the lumen equivalent of a 100W PAR30 providing both energy savings and low maintenance costs. The 20W has the lumen equivalent of a 150W halogen bulb.

FEATURES

- 1000+ lumens from 15W, 2200 lumens from 20W
- CRI of 90+
- Optical inner reflector provides precise beam control with reduced glare while the acrylic lens diffuses the light output for a halogen lamp like appearance
- Proprietary heat sink design provides superior thermal management ensuring a minimum of 50,000 hrs of operation while maintaining a minimum of 70% lumen output

SPECIFICATIONS

Input Voltage	120-277 VAC (universal)
Wattage	15W / 20W
Dimming	0-10V or Triac
Colour Temp	2700K / 3000K / 4000K / 5000K
Lumen Output	1000 lm / 2200 lm
Efficacy	86-100 lm/W
CRI	90+
Beam Angle	15° / 24° / 38° / 60°
Power Factor	0.91
Lamp Life	50,000 hours
Environment	IP20
Certification	cULus
Warranty	5 years - see published warranty terms for details

* Product specifications subject to change without notice.

ORDERING INSTRUCTIONS

MODEL	WATTAGE	COLOUR TEMP	BEAM ANGLE	DRIVER	INTERIOR FINISH	TRIM	GIMBAL FINISH	TRIM FINISH
EU-MINI								
01: 1 Light Head	15: 15W	27: 2700K	15: 15 Deg	10: Dimming 0-10V	BL: Black	T: Aluminum Trim	BL: Black	BL: Black
02: 2 Light Head	20: 20W	30: 3000K	24: 24 Deg	TR: Triac	WH: White		WH: White	WH: White
03: 3 Light Head		40: 4000K	38: 38 Deg				SL: Silver	SL: Silver
04: 4 Light Head		50: 5000K	60: 60 Deg				Anodized	

04-SQ: 4 Light Head Square

Example: EU-MINI-01-20-30-24-TR-BL-T-BL-SL = EU-MINI 1 light head, 20W, 3000K, 24 degree beam angle, triac dimming, black interior finish, aluminum trim, black gimbal finish, silver trim finish