

Type	
Project	
Catalog No.	

IMAGE



DESCRIPTION

Flexi HD
 High Density White

- Cove lighting in large commercial areas, retail, hospitality.
- Backlit Signage.
- Fluorescent replacement.
- Ambient lighting in commercial office spaces.
- Backlighting of translucent stone elements in hospitality.

Flexi MD
 Medium Density White

- Backlighting and edge lighting of glass elements and objects.
- Toe-kick lighting
- Backlighting of small objects

SPECIFICATIONS

Input Voltage	24V DC
Wattage	4w/ft (13w/m), 6w/ft (19w/m)
Colour Temp	2700K / 3000K / 3500K / 4000K / 5000K / 6000K
Lumen Output	400 lumens/ft, 600 lumens/ft
# of LEDs	73/ft (240/m)
CRI	90 ⁺
Beam Angle	120°
Lamp Life	50,000 hours
Environment	IP20
Certification	cULus
Warranty	5 years if driver supplied by Revlite
Reel Length	5m / 16.4ft

Input Voltage	24V DC
Wattage	1.5w/ft (5w/m), 3w/ft (10w/m)
Colour Temp	2700K / 3000K / 3500K / 4000K / 5000K / 6000K
Lumen Output	150 lumens/ft, 300 lumens/ft
# of LEDs	36/ft (118/m), 54/ft (177/ m), 73/ft (240/m)
CRI	90 ⁺
Beam Angle	120°
Lamp Life	50,000 hours
Environment	IP20
Certification	cULus
Warranty	5 years if driver supplied by Revlite
Reel Length	5m / 16.4ft

* Power levels of 4-6W/Ft or higher, requires an accessory heat sink for thermal stability or the life span of the LEDs will be seriously negatively affected and will not meet expected lifespan.
 * Product specifications subject to change without notice.

ORDERING INSTRUCTIONS

