



*Measurement in mm
*Cut out: Ø115



DESCRIPTION

An elegant 15W high efficiency down light fixture with 360° gimbal feature and the ability to zoom focus on objects of interest. Lumen output in excess of 1300 lumens which surpasses the output of typical 75W halogen. Lens is infinitely focusable from 15°-90°.

FEATURES

- 15 Watt LED array, CRI>80 @ 3000K
- Optional high GAI LED
- 1300+ lumens from state of the art LED COB chip
- Continuously variable beam angles from 15°-90°. By pushing or pulling the lens collar, different beam cone size and brightness levels can be realized
- Proprietary ball and socket aluminum heat sink allows 360° rotation and swivel of entire light engine to allow illumination of the wall or objects of interest
- Lens can be rotated continuously 360° in the horizontal plane and up to 25° in the vertical plane
- Heat sink is oversized to ensure maximum LED life
- LED power supplies suitable for indoor and outdoor use 120-277VAC input standard
- Finished with slim line aluminum trim for optimum aesthetics

SPECIFICATIONS

Input Voltage	120-277 VAC (universal)
Wattage	15W
Colour Temp	3000K / 3500K / 4000K
Dimming	Triac / 0-10 V
Lumen Output	1307 lumens @ 4000K
CRI	80+ / 90+ / high GAI
Beam Angle	Adjustable 15°-90°
Power Factor	≥0.9
Lamp Life	>50,000 hours
Environment	IP20
Certification	cULus
Warranty	5 years - see published warranty terms for details

* Product specifications subject to change without notice.

ORDERING INSTRUCTIONS

MODEL	COLOUR TEMP	CRI	FINISH	DRIVER
LR15-ZL	30: 3000K 35: 3500K 40: 4000K	80: 80+ 90: 90+ GA: High GAI	BK: Black WH: White SL: Silver	TR: Triac 10: 0-10 V ND: Non-dimming

Example: LR15-ZL-40-80-BK-TR = LR15-ZL, 4000K, 80+ CRI, black finish, triac dimming