

Type	
Project	
Catalog No.	

**T5 RETROFIT**


*\*Measurement in mm*




**30600 SERIES T5 RETROFIT ACCESSORIES**




**End Cap**  
 RL-EC-T5 (included)



**Heavy Duty Clip**  
 RL-T5N-C-UM



**Heavy Duty Double Wide Clip**  
 RL-T5N-DC-UM



**Tilt Stand**  
 RL-N-TL-UM



**RL-INT-36-PC**  
 36" Power Cord

**RL-INT-36-PC**  
 36" Power Cord



**RL-INT-36-PC-SWITCH**  
 36" Power Cord with Switch

**RL-INT-72-PC-SWITCH**  
 72" Power Cord with Switch



**RL-WT-M2M-J**  
 12" T5 Connector Cable

**RL-WT-M2M-J-24**  
 24" T5 Connector Cable

**RL-WT-M2M-J-36**  
 36" T5 Connector Cable

**RL-WT-M2M-J-48**  
 48" T5 Connector Cable

Type	
Project	
Catalog No.	

**FUNCTION**

- Revlite RL-T5 fixtures are line voltage and are linkable end to end to a maximum of 80'.
- High Density LEDs and Opal diffuser ensure no LED hotspots for smooth even illumination.
- Fixture chain may be hardwired into a junction box or plug and play into a standard wall outlet with an optional 3 prong plug that is available with or without a built in switch.
- Very low profile design.
- Each RL-T5 comes with mounting hardware, mounting clips and hardwire plug.
- RL-T5 may be mounted using double faced adhesive tape.
- cULus Listed , DLC Listed.

**APPLICATIONS**

- Cove Lighting
- Case Lighting, Bookcases, Store Counters and Display Lighting
- Backlighting of Signage in Restaurants, Offices and Hospitality
- Under Cabinet and Toe Kick lighting
- Retrofitting of any Existing Fluorescent Tube Lighting
- Cabinet/Closets, Workstations
- Office Cubicles

**SPECIFICATIONS**

Input Voltage	120V AC
Wattage	4.5W/ft
Colour Temp	2700K / 3000K / 4000K / 5000K / 6000K
Dimming	No
Lumen Output	475 lumens/ft
CRI	80
Beam Angle	130°
Power Factor	>0.9
Lamp Life	50,000 hours
Environment	IP20
Certification	cULus
Warranty	5 years - see published warranty terms for details

- \* Product specifications subject to change without notice.
- \* Dims: 3/4" W X 1 3/8" H
- \* Housing: Aluminum
- \* Dimming: NO
- \* Includes: RL-T5-DE-PW-CONN & RL-EC-T5
- \* For environments requiring a special listing for Damp locations or for Cabinets/Closets "Close to Clothing" contact factory.

**ORDERING INSTRUCTIONS**

MODEL	LENGTH	COLOUR TEMP	FINISH
RL-T5N	1: 12 3/8" 2: 22 3/4" 3: 36 1/2" 4: 46 1/4"	27: 2700K 30: 3000K 40: 4000K 50: 5000K 60: 6000K	W: White

\* Optional only.  
 Lumen data based on 4000K. Contact factory for higher Lumen / Wattage output options.  
 Additional power supply cables, connecting cables, hard-wire boxes sold separately.