




Type	
Project	
Catalog No.	



DESCRIPTION

Designed for new construction and retrofit applications this 457mm fixed diffuser wall sconce houses a double E26 socket in a 60W configuration. LED option is available.

FEATURES

Mechanical:

- Housing constructed of 2.0mm thick steel, powder coated for a robust long life luminaire.
- Mounting plate provides direct connection to standard junction boxes.
- UL / CSA certified.

Electrical:

- 120-VAC
- Double E26 socket
- 60Watts Maximum

Optics:

- Optical Diffuser of Polycarbonate of 3mm thickness with reduced glare
- Diffuser is 457 X 114 X 90mm and easily removable without tools

Lens:

- Standard white or opaque. Custom available.

Listings:

- Fixture is c UL us listed

Warranty:

- One (1) year warranty against defects in materials and workmanship
- Warranty period is for 5 years when installed according to Revlite installation instructions and the applicable building codes.

ORDERING INSTRUCTIONS

MODEL	TYPE	COLOUR	COLOUR TEMP	LENS	DRIVER
WS-18-4.5-4					
	E26: E26 base L : LED	BK : Black WH: White C : Custom	27: 2700K 30: 3000K 40: 4000K 50: 5000K	OP : Opaque WH: White	ND: Non Dimming 10 : 0-10V TR: Triac

EXAMPLE: WS-18-4.5-4-E26-BK-27-OP-ND = WS-18-4.5-4, E26 base, black, 2700K, opaque, non-dimming