Product: Crackling Firewood & Fir

Product#: Crackling Firewood & Fir

Revised Date: 2021-01-29 00:00

SDS v1 GHS / OSHA

Print Date: 2021-06-22 16:19

Page 1 of 8

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade Name: Crackling Firewood & Fir

Product/Sales No:

1.2 Relevant indentified product use

Intended use: Compound used in customer substance/mixture/product

1.3 Details of the manufacturer/supplier of the safety data sheet

Wellington Fragrance 33306 Glendale St. Livonia, MI 48150 734-261-5531

1.4 Emergency telephone number

(800) 255-3924 Domestic USA, Canada, Puerto Rico, and US Virgin Islands

+1 813 248-0585 International

2. Hazards Identification

2.1 Classification of the substance or mixture

This mixture has not been tested as a whole. The effects, listed below, are based on evaluation of individual components in accordance with the provisions of the regulation(s) noted below.

Classification according to GHS

Flammable Liquids, Category 4 H227 : Combustible liquid

Acute Toxicity Oral, Category 5 H303 : May be harmful if swallowed

Skin Corrosion/Irritation, Category 2 H315: Causes skin irritation

Sensitization, Skin, Category 1A H317 : May cause an allergic skin reaction

Acute Toxicity Inhalation, Category 5 H333: May be harmful if inhaled Aquatic Acute Toxicity, Category 2 H401: Toxic to aquatic life

Aquatic Chronic Toxicity, Category 3 H412: Harmful to aquatic life with long lasting effects

Classification OSHA (Provisions 1910.1200 of title 29)

Flammable Liquids, Category 4 H227 : Combustible liquid Skin Corrosion/Irritation, Category 2 H315 : Causes skin irritation

Sensitization, Skin, Category 1A H317: May cause an allergic skin reaction

Classification Other

Carcinogenicity This mixture contains ingredients identified as carcinogens, at 0.1% or greater,

by the following:None [X] ACGIH [] IARC [] NTP [] OSHA []

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Product: Crackling Firewood & Fir

Product#:

Harmful to aquatic life with long lasting effects

Revised Date: 2021-01-29 00:00

SDS v1 GHS / OSHA

Page 2 of 8

Print Date: 2021-06-22 16:19

Signal Word: Warning

Hazard statments

H227	Combustible liquid
H303	May be harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H333	May be harmful if inhaled
H401	Toxic to aquatic life

Precautionary Statements

Prevention:

H412

P235	Keep cool

P264 Wash hands thoroughly after handling
P272 Contaminated work clothing should not be allowed out of the workplace

P273 Avoid release to the environment

Response:

P302 + P352	IF ON SKIN: Wash with soap and water
P304 + P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P333 + P313	If skin irritation or a rash occurs: Get medical advice/attention
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse
P370 + P378	In case of fire: Use Carbon dioxide (CO2), Dry chemical, or Foam for extinction. Do not use

a direct water jet on burning material

2.3 Other Hazards

no data available

3. Composition/Information on Ingredients

3.1 Mixtures

This product is a complex mixture of ingredients, which contains among others the following substance(s), presenting a health or environmental hazard within the meaning of the UN Globally Harmonized System of Classification and Labeling of Chemicals (GHS):

CAS:	# edient	EC#	Conc. Range	GHS Classification
100-7		202-888-7 leneglycerol	10 - 20 %	H315; H401
1.	sopropyllu	enegiyceroi		
125-	12-2	204-727-6	5 - 10 %	H227; H316; H401
1.	sobornyl a	cetate		
97-53	3-0	202-589-1	2 - 5 %	H303; H316; H317; H319; H401
Ε	Eugenol			
105-9	95-3	203-347-8	2 - 5 %	H401
Е	thylene b	rassylate		
	-	-		

Product: **Crackling Firewood & Fir**

Product#:

Revised Date: 2021-01-29 00:00

SDS v1 GHS / OSHA

Page 3 of 8 Print Date: 2021-06-22 16:19

CAS# Ingredient	EC#	Conc. Range	GHS Classification
470-82-6	207-431-5	1 - 2 %	H226; H303; H317; H320; H402
Eucalypto	o <i>l</i>		
101-86-0	202-983-3	1 - 2 %	H303; H316; H317; H400; H411
Hexyl cin	namal		
5989-27-5	227-813-5	0.1 - 1.0 %	H226; H304; H315; H317; H400; H412
Limonene	Э		
5392-40-5	226-394-6	0.1 - 1.0 %	H313; H315; H317; H319; H401
Citral			
103-95-7	203-161-7	0.1 - 1.0 %	H227; H303; H315; H317; H401; H412
Cyclame	n Aldehyde		
80-56-8 pinene	201-291-9	0.1 - 1.0 %	H226; H302; H304; H315; H317; H400; H410
91-64-5	202-086-7	0.1 - 1.0 %	H302; H317; H402
Coumarir	7		
78-70-6	201-134-4	0.1 - 1.0 %	H227; H303; H315; H317; H319; H402
Linalool			
112-54-9	203-983-6	0.1 - 1.0 %	H315; H317; H319
Lauraldei	hyde		
110-41-8	203-765-0	0.1 - 1.0 %	H227; H315; H317; H402; H410
2-Methyli	undecanal		
103-26-4	203-093-8	0.1 - 1.0 %	H303; H317
Methyl ci	nnamate		
127-91-3	204-872-5	0.1 - 1.0 %	H226; H304; H315; H317; H400; H410
beta Pine	ene		
13466-78-9	236-719-3	0.1 - 1.0 %	H226; H303; H304; H315; H317; H332;
delta-3-C	delta-3-Carene H401; H411		H401; H411
See Section	16 for full text of	GHS classification	on codes

See Section 16 for full text of GHS classification codes which where not shown in section 2

Total Hydrocarbon Content (% w/w) = 2.20

4. **First Aid Measures**

Description of first aid measures

Inhalation: Remove from exposure site to fresh air and keep at rest.

Obtain medical advice.

Flush immediately with water for at least 15 minutes. **Eye Exposure:**

Contact physician if symptoms persist.

Skin Exposure: Remove contaminated clothes. Wash thoroughly with water (and soap).

Contact physician if symptoms persist.

Ingestion: Rinse mouth with water and obtain medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms: no data available

Product: Crackling Firewood & Fir

Product#: Crackling Firewood & Fir

Revised Date: 2021-01-29 00:00

SDS v1 GHS / OSHA

Page 4 of 8

Print Date: 2021-06-22 16:19

Risks: Refer to Section 2.2 "Hazard Statements"

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: Refer to Section 2.2 "Response"

5. Fire-Fighting measures

5.1 Extinguishing media

Suitable: Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable Do not use a direct water jet on burning material

5.2 Special hazards arising from the substance or mixture

During fire fighting: Water may be ineffective

5.3 Advice for firefighters

Further information: Standard procedure for chemical fires

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation and contact with skin and eyes. A self-contained breathing apparatus is recommended in case of a major spill.

6.2 Environmental precautions

Keep away from drains, soil, and surface and groundwater.

6.3 Methods and materials for containment and cleaning up

Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapors. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

6.4 Reference to other sections

Not Applicable

7. Handling and Storage

7.1 Precautions for safe handling

Apply according to good manufacturing and industrial hygiene practices with proper ventilation. Do not drink, eat or smoke while handling. Respect good personal hygiene.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry and ventilated area away from heat sources and protected from light in tightly closed original container. Avoid uncoated metal container. Keep air contact to a minimum.

7.3 Specific end uses

No information available

Product: **Crackling Firewood & Fir**

Product#:

Revised Date: 2021-01-29 00:00

SDS v1 GHS / OSHA

Page 5 of 8 Print Date: 2021-06-22 16:19

Exposure Controls/Personal Protection 8.

8.1 Control parameters

Exposure Limits:

ACGIH ACGIH OSHA OSHA Component TWA ppm STEL ppm TWA ppm STEL ppm

80-56-8 pinene 20 127-91-3 beta Pinene 20 20 13466-78-9 delta-3-Carene

Engineering Controls: Use local exhaust as needed. 8.2 Exposure controls - Personal protective equipment

Eye protection: Tightly sealed goggles, face shield, or safety glasses with brow guards and side shields, etc.

as may be appropriate for the exposure

Avoid excessive inhalation of concentrated vapors. Apply local ventilation where appropriate. Respiratory protection:

Skin protection: Avoid Skin contact. Use chemically resistant gloves as needed.

9. **Physical and Chemical Properties**

9.1 Information on basic physical and chemical properties

Appearance: Liquid

Odor: Conforms to Standard Color: Conforms to Standard

Viscosity: Liquid

Not determined **Freezing Point: Boiling Point:** Not determined **Melting Point:** Not determined Flashpoint (CCCFP): 190 F (87.78 C) Not determined Auto flammability: **Explosive Properties:** None Expected Oxidizing properties: None Expected

Vapor Pressure (mmHg@20 C): 0.0555 %VOC: 4.50

Specific Gravity @ 25 C: Not determined Density @ 25 C: Not determined Refractive Index @ 20 C: Not determined Soluble in: Not determined

10. Stability and Reactivity

10.1 Reactivity None 10.2 Chemical stability Stable

Product: Crackling Firewood & Fir

Product#: Crackling Firewood & Fir

Revised Date: 2021-01-29 00:00

SDS v1 GHS / OSHA

Print Date: 2021-06-22 16:19

Page 6 of 8

10.3 Possibility of hazardous reactions None known10.4 Conditions to avoid None known

10.5 Incompatible materialsStrong oxidizing agents, strong acids, and alkalis

10.6 Hazardous decomposition products None known

11. Toxicological Information

11.1 Toxicological Effects

Acute Toxicity Estimates (ATEs) based on the individual Ingredient Toxicity Data utilizing the "Additivity Formula"

Acute toxicity - Oral - (Rat) mg/kg (LD50: 4766.9134) May be harmful if swallowed

Acute toxicity - Dermal - (Rabbit) mg/kg

Not classified - the classification criteria are not met

Acute toxicity - Inhalation - (Rat) mg/L/4hr (LD50: 410.1233) May be harmful if inhaled

Skin corrosion / irritation Causes skin irritation

Serious eye damage / irritation

Not classified - the classification criteria are not met

Respiratory sensitization

Not classified - the classification criteria are not met

Skin sensitization May cause an allergic skin reaction

Germ cell mutagenicity

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Aspiration hazard Not classified - the classification criteria are not met

12. Ecological Information

12.1 Toxicity

Acute acquatic toxicity

Toxic to aquatic life

Chronic acquatic toxicity Harmful to aquatic life with long lasting effects

Toxicity Data on soilno data availableToxicity on other organismsno data available

12.2 Persistence and degradabilityno data available12.3 Bioaccumulative potentialno data available12.4 Mobility in soilno data available12.5 Other adverse effectsno data available

Product: **Crackling Firewood & Fir**

Revised Date: 2021-01-29 00:00

SDS v1 GHS / OSHA

Page 7 of 8

Print Date: 2021-06-22 16:19

13. **Disposal Conditions**

13.1 Waste treatment methods

Do not allow product to reach sewage systems. Dispose of in accordance with all local and national regulations. Send to a licensed waste management company. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.

14. Transport Information

Marine Pollutant Nο

UN-nr. Regulator Class **Pack Group** Sub Risk

U.S. DOT (Non-Bulk) Not Regulated - Not Dangerous Goods

Product#:

Chemicals NOI

ADR/RID (International Road/Rail) Not Regulated - Not Dangerous Goods

Chemicals NOI

IATA (Air Cargo) Not Regulated - Not Dangerous Goods

Chemicals NOI

IMDG (Sea) Not Regulated - Not Dangerous Goods

Chemicals NOI

15. **Regulatory Information**

U.S. Federal Regulations

TSCA (Toxic Substance Control Act) All components of the substance/mixture are listed or exempt

40 CFR(EPCRA, SARA, CERCLA and CAA) This product contains NO components of concern.

U.S. State Regulations

California Proposition 65 Warning This product contains the following components:

123-35-3(NF 204-622-5 0.01 - 0.1% beta-Myrcene (Natural Source)

205-427-8 <= 8 ppm 140-67-0 Estragole (Methyl chavicol) (Natural Source)

Pulegone (Natural Source) 89-82-7 201-943-2 <= 5 ppm

Canadian Regulations

DSL 100.00% of the components are listed or exempt.

16. Other Information

GHS H-Statements referred to under section 3 and not listed in section 2

H226: Flammable liquid and vapour H302: Harmful if swallowed

H304 : May be fatal if swallowed and enters airways H313: May be harmful in contact with skin

H317: May cause an allergic skin reaction H316: Causes mild skin irritation H319: Causes serious eye irritation H320: Causes eye irritation

H332: Harmful if inhaled H400: Very Toxic to aquatic life

H402: Harmful to aquatic life H410: Very toxic to aquatic life with long lasting

effects

H411: Toxic to aquatic life with long lasting effects

Product: Crackling Firewood & Fir

Product#:

Revised Date: 2021-01-29 00:00

SDS v1 GHS / OSHA

Print Date: 2021-06-22 16:19

Page 8 of 8

Total Fractional Values

(TFV) Risk

(12.19) Acute Toxicity Inhalation, Category 5

(7.00) Sensitization, Skin, Category 1A

(2.65) Skin Corrosion/Irritation, Category 3

(2.24) Aquatic Acute Toxicity, Category 2

(1.05) Acute Toxicity Oral, Category 5

(TFV) Risk

(7.00) Sensitization, Skin, Category 1

(5.87) Aquatic Chronic Toxicity, Category 3

(2.40) Sensitization, Skin, Category 1B

(1.47) Skin Corrosion/Irritation, Category 2

Remarks

This safety data sheet is based on the properties of the material known to Wellington Fragrance at the time the data sheet was issued. The safety data sheet is intended to provide information for a health and safety assessment of the material and the circumstances, under which it is packaged, stored or applied in the workplace. For such a safety assessment Wellington Fragrance holds no responsibility. This document is not intended for quality assurance purposes.