

XLT-30

ACOUSTICAL LEAK DETECTOR

NEW MULTI-SENSOR - Option B



BIG FOOT & HYDROPHONIC PROBE SENSOR - Option A



LITTLE FOOT & HYDROPHONIC SENSOR - Option C



Fisher's XLT-30 leak detector is built to perform and priced to compete. With advanced electronic amplification and filtering, an all tactile keypad, an easy to read digital display, and notch feature (which allows independent suppression of outside interfering noise) the XLT-30 proves its worth again and again.

Fisher's XLT-30 is available in 3 options: Option A with a Bigfoot Hydrophonic probe sensor, Option B with Fisher's New Multi-Sensor, & Option C with the Littlefoot Hydrophonic Probe.

In the Fisher tradition, the XLT-30 is affordable, tough, and simple to use while providing maximum performance. A two year limited warranty comes standard with the unit.

Features

- Detects and pinpoints liquid leaks in pipes
- Notch filter for external noise suppression
- Ultra low amplifier noise
- Peak hold feature on LCD bargraph for sound comparison
- Automatic limiter system to enhance weak noise sources
- Rugged membrane keypad and LCD display with backlight
- Increased response in poor sound conductors
- Shielded sensor for reduced response to outside noise
- Improved headset for clearer sound response
- Automatic battery test and monitoring
Operates on two 9 volt batteries



200 W. Willmott Rd., Los Banos, CA 93635-5501

T 209.826.3292 F 209.826.0416 www.fisherlab.com info@fisherlab.com

Fisher Labs has been serving the demanding needs of the utility industry with innovative locating solutions - Since 1931. From pipe & cable locators, valve & box locators, sound & leak detectors to water level indicators, Find it... with Fisher!

XLT-30 specifications



Specifications subject to change without notice.

Operating frequency: 60 Hz – 6 kHz, Gain = 95 db
 20 Hz – 60 Hz, Gain ≥ 90 dB

Filter types and frequency ranges:

- All Pass: 60 Hz to 6 kHz
 - Low Pass: Adjustable cut-off frequency from 150 Hz to 2.4 kHz
 - High Pass: Adjustable pass-band frequency from 150 Hz to 2.4 kHz
 - Band Pass: Adjustable center frequency from 150 Hz to 2.4 kHz
 - Notch Filter: Adjustable center frequency rejection from 150 Hz to 2.4 kHz
- Can be used simultaneously with any filter option

Indication of output:

- Audio: High performance head phones (64 ohms)
- Visual: LCD bar graph display w/2 digit numerical read out

Grade of protection: Splash proof
 Battery test Automatic
 Type of Battery/Quantity Alkaline 9 volt, 2
 Battery life: Approximately 50 hours

WEIGHT:

Option “A” w/Big Foot	Option “B” w/Multi-Sensor	Option “C” w/Little Foot
19 lbs	10 lbs	9.5 lbs

STANDARD EQUIPMENT:

Option “A”	Option “B”	Option “C”
Heavy-duty carrying case	Heavy-duty carrying case	Heavy-duty carrying case
Operation manual	Operation manual	Operation manual
Control unit	Control unit	Control unit
Head phones	Head phones	Head phones
Big Foot	Multi-Sensor	Little Foot
Hydrophonic Cylinder Probe	Carry Strap	Hydrophonic Cylinder Probe
“T” Handle	Housing Bracket	Probe Cable Assembly
Probe Cable Assembly	Probe Cable Assembly	“T” Handle
Carry Strap	Sound Rods	Carry Strap
Housing Bracket		Housing Bracket
Sound Rods		Sound Rods



2-Year Warranty

Fisher warrants the XLT-30 to be free of defects in materials and workmanship when it is shipped from the factory. The terms of this warranty are fully explained in a warranty registration card that accompanies the instrument. Complete factory and field service facilities support the warranty.

*Warranty may vary outside the U.S. See your distributor for details.

Ordering Information

US, Mexico & Canadian Customers Contact:

FISHER LABS
 200 W. Willmott Rd.,
 Los Banos, CA 93635-5501
 T 209.826.3292 F 209.826.0416
 info@fisherlab.com www.fisherlab.com

All Other Countries Contact:

Export Department
 280 State Street, Suite 202
 North Haven, CT 06473 USA,
 T 203.230.4130 F 203.248.8093
 email: fisher@exportdept.com

