
JW FISHERS MFG INC 1953 COUNTY ST. E. TAUNTON, MA 02718 USA

(508) 822-7330; (800) 822-4744; FAX (508) 880-8949 Email: jwfishers@aol.com WEB: www.jwfishers.com

TECHNICAL DATA SHEET




- VERY SENSITIVE
- **CAN TOW UP TO THREE SEARCH COILS**
- 16 foot x 24 foot DETECTION AREA
- DETECTS ALL METALS
- 150-300 feet OF CABLE
- 1-4 MPH TOW SPEED
- 2 YEAR WARRANTY



PULSE 12 Boat Towed Detector

Fishers top of the line boat towed pulse induction metal detector detects both ferrous (iron/steel) and nonferrous (gold/silver/aluminum/bronze/etc.) metals. The PULSE 12 is the most powerful towed underwater "all metals" detector on the market today. The system has a very large detection envelope with good detection capabilities in salt water and even greater range in fresh water or on land. The Pulse 12 comes with a Control Box, a Search Coil with 150 feet of cable, and a Fish. The Search Coil mounts on the Fish and is towed through the water at 1-4 mph. The Control Box has inputs for three Search Coils. Two additional Search Coils can be added at any time and come complete with cable and fish. The additional Coils allow larger areas to be covered. One Fish is towed directly behind the center of the boat and the other Fish are towed to each side of the boat. One, two, or three Fish can be operating at the same time. When using multiple Fish, each has its own controls and meter on the Control Box. An alarm sounds and the meter swings up when any of the Search Coils detect a target. The complete system is powered by two 12 volt batteries. An Altimeter can be attached to the Fish to inform the operator of the distance between the Fish and the bottom. The PULSE 12 is covered by a TWO YEAR WARRANTY.

MAX DETECTION ENVELOPE (fresh water)



SPECIFICATIONS

SPECIFICATIONS ————			
	SENSITIVITY (in water):		H SALT
		17 in.	
		40 in.	
	One gallon can	6 ft.	4 ft.
		13 ft.	
	Ship (max. range)	16 ft.	14 ft.
	PERFORMANCE/DESCR	IPTIONS:	
	 Max detection area (fresh water) 16	ft deep, 24 ft. wide.
		············	
	• Input voltage		24 vdc.
	Readout		Meter and audio.
	DIMENSIONS/WEIGHTS:	: 24"W x 36"L	10 lba
		24 vv x 36 L 4'L x 4.5"Dia	
		14"L x 10"W x 6"H . 75"D x 150'-300' .	
			10-32 108.
	• Shipping Boxes:	60"L x 11"W x 13"H	49 lbc
		41"L x 30"W x 8"H .	
	-coii, cable, CD	41 L X 30 W X O II.	75-90 105.
	MATERIALS/COLOR:		
	• Fish	High impact P\	/C,stainless/yellow.
		High impact U/W Kinetic	
		8 conductor in po	
		High impact	

OPTIONS

- Additional Search Coils
- Altimeter
- Downrigger
- 300 foot cable
- RS232
- 0-5 vdc Analog Output

1100 GW2000/PM4/DS