

PK-500 is the “Plumber’s Kit”

This multi-purpose kit is specifically designed for professional plumbers who require both Sonde/Camera and Magnetic Locating.

The Kit includes a XT-512 Sonde & Camera Locator and a GA-92XTd Magnetic Locator.



Optimized for:

- ▶ Blockages in Steel Water Pipes
- ▶ Sondes & Cameras
- ▶ Plastic Pipe w/ Tracer Wire
- ▶ Well Casings & Irrigation Lines
- ▶ Manhole Covers & Septic Tanks



“I don’t use a sonde often, but things went perfectly! We taped the sonde to a jetter and tracked it as it was fed down the line (which went under a business that was built over a section of the pipeline after it was laid). Once I pinpointed the sonde with the XT receiver, we further pinpointed it with the Schonstedt magnetic locator they already owned.”

—Brent Hutchins, Brad Greer & Associates

The PK-500 Kit includes:

- ▶ GA-92XTd Magnetic Locator
- ▶ XT-512 Sonde and Camera Locator
- ▶ Holster
- ▶ Soft Carrying Case



XT512



Extends for greater sensitivity



GA-92XTd MAGNETIC LOCATOR



Retracts for easier carrying



XT-512 Receiver Specifications

Operating Frequency:	512 Hz plus 50/60 Hz passive detection
Battery:	One 9V Battery
Battery Life:	18 Hours (intermittent use)
LCD Display:	3.5" Digit Reflective Signal Strength, Directional Arrows, Battery Status, Volume and Depth on Sonde
Controls:	ON/Volume adjustment, OFF, DEPTH, SONDE, AUTO GAIN, UP gain, DOWN gain, PASSIVE
Dimensions:	Extended: 27.7 in (70 cm) Retracted: 17.5 in (44 cm)
Weight:	2.5 lbs (1.1 kg)
Operating Temperature:	-4°F to 140°F (-20°C to 70°C)
Water & Dust Resistance:	Rated IP54

The XT-512 pipe locator combines the portability of an expanding/retracting pistol-grip locator with a 512 Hz sonde and passive locating capability. With the XT-512, you can quickly locate pipes and find obstructions and blockages.

GA-92XTd Receiver Specifications

Gain:	4-Level LCD: Low (L), Medium (M), High (H), Extra High (XH)
Volume:	3 Levels: Muted, Medium and Maximum
Battery:	One 9V Battery
Battery Life:	24 Hours (intermittent usage)
Battery Indicator:	4-segment LCD
Nominal Sensor Spacing:	9.5" (24 cm)
Dimensions:	Extended: 26" (66 cm) Retracted: 17.5" (44 cm)
Weight:	2.4 lbs (1.1 kg)
Operating Temperature:	-13° F to 140° F (-25° C to 60° C)
Water & Dust Resistance:	Rated IP54

The GA-92XTd magnetic locator is a pistol-grip locator that extends to find underground metal objects with outstanding precision, and retracts for easy carrying in a holster.

Copyright © 2018 Schonstedt Instrument Company. All rights reserved. Schonstedt is a subsidiary of SPX Corporation. Due to a policy of continued development, we reserve the right to alter or amend any published specification without notice. This document may not be copied, reproduced, transmitted, modified or used, in whole or in part, without the prior written consent of Schonstedt Instrument Company.

SCHONSTEDT®

Contact Us:

800-999-8280
schonstedt.info@spx.com

Find Your Local Dealer:

schonstedt.com