AHD Dual Lens DVR Camera





This AHD (Analog High-Definition) dual lens DVR camera is compatible with our MobileMule™ Mobile DVR Series. Front Camera is equipped with 6 infra-red illuminators and a wide 130° viewing angle. Rear Camera features a wide 92° viewing angle.

RVS-818-AHD also features a simple installation with included 3M mounting sticker. This two camera system uses two MobileMule™ video inputs.

## **CAMERA SPECIFICATIONS**

S/N RATIO

INFRA-RED

NEXT CHIP 2431H	AUDIO	SUPPORTS AUDIO
SONY IMX225	VIEWING ANGLE	FRONT CAMERA: 130°
PAL/NTSC	130 executable i nervisience verte.	REAR CAMERA: 92°
FRONT CAMERA: 2.1MM	POWER SUPPLY	12V DC ±10%
REAR CAMERA: 2.8MM	DIMENSIONS	5" (L) X 1.1" (H) X 3.9" (D)
600 TV LINES	WEIGHT	200G
PAL: 500 (H) X 582 (V)	OPERATING TEMPERATURE	-20°C ~ +50°C
		<95%
	16 2000 0100 0000 0000 0000	A1100 074
REAR CAMERA: 2.8MM	1	
0.01LUX @ (F1.2, AGC ON)		
	SONY IMX225 PAL/NTSC FRONT CAMERA: 2.1MM REAR CAMERA: 2.8MM 600 TV LINES PAL: 500 (H) X 582 (V) NTSC: 510 (H) X 492 (V) FRONT CAMERA: 2.1MM REAR CAMERA: 2.8MM	SONY IMX225 PAL/NTSC FRONT CAMERA: 2.1MM REAR CAMERA: 2.8MM 600 TV LINES PAL: 500 (H) X 582 (V) NTSC: 510 (H) X 492 (V) FRONT CAMERA: 2.1MM REAR CAMERA: 2.8MM  VIEWING ANGLE POWER SUPPLY DIMENSIONS WEIGHT OPERATING TEMPERATURE OPERATING HUMIDITY

MORE THAN 72DB

6 INFRA-RED LIGHTS

(AGC OFF)

5M RANGE