

ENG



**Hot Water
Electric Powered
Natural Gas or LP Heated**

Small in size but big on innovation and quality, the ENG series provides a lot of bang for the buck. There isn't a more compact, natural gas pressure washer on the market. The ENG packs a ton of features into an incredibly tiny footprint, including our patented Cool-Bypass system which keeps water temperature low while the machine is in bypass mode, helping to extend the life of the pump. Other innovative options include Landa's Tru-Tite belt tensioning system to reduce wear and tear on the belt, and the versatile Fielder's Choice system, allowing users to switch the inlet/outlet connections from one side to the other. If you're tight on space but have big cleaning needs, the ENG is the perfect machine for you.

- Up to 9.5 GPM / 3,000 PSI
- Compact Stationary Design
- Natural Gas or LP Heated
- Optional Remote Operation



Model #	NG Part #	LP Part #	GPM	PSI	Pump RPM	Pump	NG BTU*	Motor HP	Volts	Phase	Amps	Ship Wt (lbs)
ENG4-20024A	1.109-800.0	1.109-837.0	3.5	2000	1350	LB4025R	310,000	5.0	230	1	25	815
ENG4-22024A	1.109-801.0	1.109-838.0	4.0	2200	1250	LM4035R	364,000	6.2	230	1	29	843
ENG4-22024B	1.109-802.0	1.109-839.0	4.0	2200	1250	LM4035R	364,000	6.2	230	3	16	843
ENG4-22024C	1.109-803.0	1.109-840.0	4.0	2200	1250	LM4035R	364,000	6.2	460	3	7	843
ENG4-22024F	1.109-804.0	1.109-841.0	4.0	2200	1250	LM4035R	364,000	6.2	575	3	6.5	843
ENG4-22024G	1.109-805.0	1.109-842.0	4.0	2200	1250	LM4035R	364,000	6.2	208	1	30	843
ENG4-22024H	1.109-806.0	1.109-843.0	4.0	2200	1250	LM4035R	364,000	6.2	208	3	18	843
ENG4-30024A	1.109-807.0	1.109-844.0	3.9	3000	1225	LM4035R	354,000	8.2	230	1	36	856
ENG4-30024B	1.109-808.0	1.109-845.0	3.9	3000	1225	LM4035R	354,000	8.2	230	3	25	856
ENG4-30024C	1.109-809.0	1.109-846.0	3.9	3000	1225	LM4035R	354,000	8.2	460	3	11	856
ENG4-30024F	1.109-810.0	1.109-847.0	3.9	3000	1225	LM4035R	354,000	8.2	575	3	14	856
ENG4-30024G	1.109-811.0	1.109-848.0	3.9	3000	1225	LM4035R	354,000	8.2	208	1	38	856
ENG4-30024H	1.109-812.0	1.109-849.0	3.9	3000	1225	LM4035R	354,000	8.2	208	3	27	856
ENG5-23024A	1.109-813.0	1.109-850.0	5.0	2300	1200	LT6035R	439,000	8.2	230	1	36	856
ENG5-23024B	1.109-814.0	1.109-851.0	5.0	2300	1200	LT6035R	439,000	8.2	230	3	25	856
ENG5-23024C	1.109-815.0	1.109-852.0	5.0	2300	1200	LT6035R	439,000	8.2	460	3	11	856
ENG5-23024F	1.109-816.0	1.109-853.0	5.0	2300	1200	LT6035R	439,000	8.2	575	3	14	856
ENG5-23024G	1.109-817.0	1.109-854.0	5.0	2300	1200	LT6035R	439,000	8.2	208	1	38	856
ENG5-23024H	1.109-818.0	1.109-855.0	5.0	2300	1200	LT6035R	439,000	8.2	208	3	27	856
ENG5-30024A	1.109-819.0	1.109-856.0	4.8	3000	1160	LT6035R	415,000	10.0	230	1	42	885
ENG5-30024B	1.109-820.0	1.109-857.0	4.8	3000	1160	LT6035R	415,000	10.0	230	3	26	885
ENG5-30024C	1.109-821.0	1.109-858.0	4.8	3000	1160	LT6035R	415,000	10.0	460	3	15	885
ENG5-30024F	1.109-822.0	1.109-859.0	4.8	3000	1160	LT6035R	415,000	10.0	575	3	14	885
ENG5-30024G	1.109-823.0	1.109-860.0	4.8	3000	1160	LT6035R	415,000	10.0	208	1	49	885
ENG5-30024H	1.109-824.0	1.109-861.0	4.8	3000	1160	LT6035R	415,000	10.0	208	3	32	885

Dimensions: 49"L x 24"W x 48"H * See product bid specifications for details regarding LP BTUs. Ratings may vary.

ENG



**Hot Water
Electric Powered
Natural Gas or LP Heated**

Small in size but big on innovation and quality, the ENG series provides a lot of bang for the buck. There isn't a more compact, natural gas pressure washer on the market. The ENG packs a ton of features into an incredibly tiny footprint, including our patented Cool-Bypass system which keeps water temperature low while the machine is in bypass mode, helping to extend the life of the pump. Other innovative options include Landa's Tru-Tite belt tensioning system to reduce wear and tear on the belt, and the versatile Fielder's Choice system, allowing users to switch the inlet/outlet connections from one side to the other. If you're tight on space but have big cleaning needs, the ENG is the perfect machine for you.



- Up to 9.5 GPM / 3,000 PSI
- Compact Stationary Design
- Natural Gas or LP Heated
- Optional Remote Operation

Model #	NG Part #	LP Part #	GPM	PSI	Pump RPM	Pump	NG BTU*	Motor HP	Volts	Phase	Amps	Ship Wt (lbs)
ENG6-32024B	1.109-825.0	1.109-862.0	6.3	3200	1525	LT6035R	507,000	15.0	230	3	39	1825
ENG6-32024C	1.109-826.0	1.109-863.0	6.3	3200	1525	LT6035R	507,000	15.0	460	3	19	1825
ENG6-32024F	1.109-827.0	1.109-864.0	6.3	3200	1525	LT6035R	507,000	15.0	575	3	18	1825
ENG6-32024H	1.109-828.0	1.109-865.0	6.3	3200	1525	LT6035R	507,000	15.0	208	3	39	1825
ENG8-32024B	1.109-829.0	1.109-866.0	8.0	3200	1370	LX9536R	658,000	20.0	230	3	46	1840
ENG8-32024C	1.109-830.0	1.109-867.0	8.0	3200	1370	LX9536R	658,000	20.0	460	3	26	1840
ENG8-32024F	1.109-831.0	1.109-868.0	8.0	3200	1370	LX9536R	658,000	20.0	575	3	21	1840
ENG8-32024H	1.109-832.0	1.109-869.0	8.0	3200	1370	LX9536R	658,000	20.0	208	3	60	1840
ENG10-30024B	1.109-833.0	1.109-870.0	9.5	3000	1400	LX1036R	816,000	20.0	230	3	52	1910
ENG10-30024C	1.109-834.0	1.109-871.0	9.5	3000	1400	LX1036R	816,000	20.0	460	3	26	1910
ENG10-30024F	1.109-835.0	1.109-872.0	9.5	3000	1400	LX1036R	816,000	20.0	575	3	21	1910
ENG10-30024H	1.109-836.0	1.109-873.0	9.5	3000	1400	LX1036R	816,000	20.0	208	3	60	1910

Dimensions: 64"L x 35"W x 61"H *See product bid specifications for details regarding LP BTUs. Ratings may vary.

Field Installed Options & Accessories

- 8.917-509.0 LanCom Wireless Remote System
- 8.921-832.0 Additional LanCom Wireless Remote
- 8.917-817.0 LanCom Wireless Remote Wall Mount Bracket
- 8.921-773.0 Wired Remote Control Kit for Detergent (requires 8.921-774.0)
- 8.921-774.0 Wired Remote Control Kit for Pump & Burner (NOTE: cord length is 20')
- 8.922-157.0 Remote Control Box (for additional wired remotes only)
- 8.917-507.0 Snap-N-Go Auto Start/Stop Kit w/ Lock Out (no remote, or wireless remote)
- 9.807-646.0 Snap-N-Go Auto Start/Stop Kit w/o Lock Out (wired remote, requires 8.921-774.0)

Field Installed Options & Accessories

- 8.917-508.0 Snap-N-Go Time Delay Kit
- 8.921-776.0 Steam Combo Kit
- 9.801-040.0 Draft Diverter, 10" (Fits 4 and 5 GPM Models)
- 8.717-730.0 Draft Diverter, 12" (Fits 6, 8 and 10 GPM Models)
- 8.753-474.0 Draft Damper, 10"
- 8.753-478.0 Draft Damper, 12"
- 8.753-707.0 Reducer, Stack 10" to 8"
- 8.753-706.0 Reducer, Stack 12" to 10"
- 8.923-213.0 Fielder's Choice System