

MHC



Hot Water Gas Powered Diesel/Oil Heated

With a rugged frame, stainless steel top wrap, and 13" flat-free tires, the MHC is both durable and portable, and easy to maneuver over flat surfaces and around corridors and hallways. The control panel is strategically located, allowing you to easily adjust the thermostat and hour meter depending on your needs. A technologically advanced engine-and-regulator combination eliminates the need for a battery or electrical connection, making it a convenient and versatile on-site choice for keeping your restaurant, resort, spa, or hotel clean and inviting!

- Up to 3.5 GPM / 3,500 PSI
- Direct-Drive or Belt-Drive Pump
- Diesel/Oil Heated
- Engine-Regulator Combination



Model MHC3-24324



Model #	Part #	GPM	PSI	Pump RPM	Pump Drive	Pump	Engine	CCs	Ship Wt (lbs)
MHC3-24324	1.110-087.0	2.7	2400	3400	Direct	LPP2535G	Honda GX200	196	560
MHC4-30324E/S	1.110-041.0	3.5	3000	3400	Direct	LS3540G3	Honda GX390	389	600
MHC4-35324E	1.110-042.0	3.5	3500	3400	Direct	LS3540G3	Honda GX390	389	600
MHC4-35324E	1.110-084.0	3.5	3500	3400	Direct	LS3540G3	Vanguard 400	408	600
MHC4-35324E/B	1.110-077.0	3.5	3500	1800	Belt	LS3540L.3	Honda GX390	389	600
MHC4-35324E/B	1.110-081.0	3.5	3500	1800	Belt	LS3540L.3	Vanguard 400	408	600

Dimensions: 52"L x 29"W x 45"H

Field Installed Options & Accessories

8.915-496.0	360° Pivot Hose Reel Kit (100' capacity, reel only)
8.750-487.0	Pivot Hose Reel (100' capacity, reel only)
8.750-477.0	Non-Pivot Hose Reel (100' capacity, reel only)
8.917-541.0	Hose Reel Platform with E-Zee Reel & Plumbing (holds 100' of 3/8" hose, not included)*
8.931-592.0	Support, Rotary Hose Reel for MHC w/GX200 engine**
8.917-522.0	Hose Reel Platform Only*
8.915-404.0	Wheel Kit (2 front caster wheels)
8.915-406.0	Float Tank & Inlet Detergent Valve
8.931-584.0	Float Tank for MHC w/GX200 engine**
8.916-184.0	Lifting Bracket
8.915-494.0	Trailer Mount Kit

* Should not be used as a lifting rack / **For use with model MHC3-24324 only.

