











Cold Water Electric Powered

The PE is one of our most popular machines for everyday use. Only the highest-quality components are used on the PE, including our tri-plex high-pressure pump with 7-year warranty, industrialduty Baldor motor, durable steel frame with welded seams, and a stainless steel point and shoot wand for cleaning effectiveness. The PE has a 24-inch hose guard for burst protection and trilingual operating instructions for owner liability assurance. Reduce cleaning time with features like front and back handles, leak-free pneumatic tires, and shock-absorbing, spring-loaded rubber feet to prevent "walking" while in operation.

- Up to 4.8 GPM / 3,000 PSI
- Belt-Drive Pump
- Steel Chassis with Weather-Resistant Finish

Model #	Part #	GPM	PSI	Pump RPM	Pump	Motor HP	Volts	Phase	Amps	Ship Wt (lbs)
PE2A-15024D*	1.106-105.0	1.8	1500	1650	LB3030R	2.0	120	1	21	193
PE3-11024D	1.106-009.0	2.8	1000	1540	LB3030R	2.0	120	1	20	193
PE4-20024A	1.106-010.0	4.2	2000	900	LT6036R.2	6.2	230	1	27	285
PE4-20024B	1.106-011.0	4.2	2000	900	LT6036R.2	6.2	230	3	16	265
PE4-20024C	1.106-012.0	4.2	2000	900	LT6036R.2	6.2	460	3	8	266
PE4-30024A	1.106-013.0	3.5	3000	800	LT6036R.2	7.5	230	1	36	337
PE4-30024B	1.106-014.0	3.5	3000	800	LT6036R.2	7.5	230	3	21.5	270
PE4-30024C	1.106-015.0	3.5	3000	800	LT6036R.2	7.5	460	3	10.5	280
PE5-30024B	1.106-016.0	4.8	3000	1060	LT6036R.2	10.0	230	3	26.8	290
PE5-30024C	1.106-017.0	4.8	3000	1060	LT6036R.2	10.0	460	3	13.4	285

Dimensions: 48"L x 28"W x 28"H PE3 44"L x 28"W x 26"H

^{*} PE2A-15024D comes equipped with Auto Start/Stop, two yellow nozzles, two green nozzles, and a variable pressure wand. Contact your local dealer for more details.