

PHW



**Hot Water
Electric Powered
Diesel/Oil Heated**

The PHW is our flagship workhorse, featuring patented Cool-Bypass* technology that limits temperature buildup in the pump during periods of inactivity, prolonging the life of the equipment. It also offers innovative Snap 'N Go kits, which allow easy upgrades to time delay shutdown, wireless remote operation, or auto start-stop. This industrial series includes our large frame LT Pump affixed to our proprietary Tru-Trac belt tension system, and an oversized 10-gallon diesel fuel capacity allows you to complete challenging cleaning jobs without interruption. The integrated float tank and metering valve allows for the easy introduction of detergents when needed. Whether cleaning hog confinements, farm equipment, or fleet vehicles, the PHW is built to deliver top quality cleaning results.

- Up to 4.8 GPM / 3,000 PSI
- Belt-Drive or Direct-Drive Pump
- Diesel/Oil Heated
- Electric Motor

Optional hose reel



*Patent US 8,496,188 B2



Model #	Part #	GPM	PSI	Pump RPM	Pump	Motor HP	Volts	Phase	Amps	Ship Wt (lbs)
PHW3-11024D	1.109-078.0	2.8	1000	1725	LB3030R	2.0	120	1	20	590
PHW4-22024A	1.109-079.0	4.0	2200	1025	LT6036R.2	6.2	230	1	29	625
PHW4-22024B	1.109-080.0	4.0	2200	1025	LT6036R.2	6.2	230	3	19	610
PHW4-22024C	1.109-081.0	4.0	2200	1025	LT6036R.2	6.2	460	3	11	615
PHW4-22024F	1.109-082.0	3.5	2200	940	LT6036R.2	5.0	575	3	10	615
PHW4-22024G	1.109-083.0	4.0	2200	1025	LT6036R.2	6.2	208	1	31	625
PHW4-22024H	1.109-084.0	4.0	2200	1025	LT6036R.2	6.2	208	3	21	610
PHW4-30024A	1.109-085.0	3.9	3000	975	LT6036R.2	8.2	230	1	38	640
PHW4-30024B	1.109-086.0	3.9	3000	975	LT6036R.2	8.2	230	3	24	625
PHW4-30024C	1.109-087.0	3.9	3000	975	LT6036R.2	8.2	460	3	12	635
PHW4-30024F	1.109-088.0	3.5	3000	975	LT6036R.2	7.5	575	3	12	635
PHW4-30024G	1.109-089.0	3.9	3000	975	LT6036R.2	8.2	208	1	40	640
PHW4-30024H	1.109-090.0	3.9	3000	975	LT6036R.2	8.2	208	3	26	625
PHW5-30024B	1.109-091.0	4.8	3000	1500	LT6036R.2	10.0	230	3	30	625
PHW5-30024C	1.109-092.0	4.8	3000	1500	LT6036R.2	10.0	460	3	16	635

Dimensions: 52"L x 32"W x 38"H

Field Installed Options & Accessories

- 8.917-509.0 LanCom Wireless Remote Control Kit
- 8.725-709.0 Additional LanCom Remote
- 8.917-817.0 LanCom Wall Mount Bracket
- 8.917-507.0 Snap-N-Go Auto Start/Stop Kit
- 8.917-508.0 Snap-N-Go Time Delay Kit
- 8.750-487.0 Pivot Hose Reel (100' capacity, reel only)
- 8.750-477.0 Non-Pivot Hose Reel (100' capacity, reel only)

Field Installed Options & Accessories

- 8.917-798.0 Wheel Kit (2 casters)
- 8.758-460.0 13" Flat-Free Tire (qty 1)
- 8.917-683.0 Steam Combo Kit
- 8.917-714.0 Lifting Bracket/Hose Reel Platform Only
- 8.917-713.0 Lifting Bracket/Hose Reel Platform with E-Zee Reel & Plumbing (holds 100' of 3/8" hose, not included)