

SEA



Cold Water Electric Powered

This top-of-the-line stationary cold-water series features a heavy-duty stainless steel or mild steel cabinet and comes standard with an insulated variable pressure wand, 50' of hose, and time delay shutdown. Available options include our LanCom wireless remote control, floor stand, and wall mount bracket assembly. This unit is ideal for cleaning a variety of indoor surfaces, and can be plumbed for plug-and-wash outdoor applications as well.

- Up to 4.2 GPM / 3,000 PSI
- Belt-Drive Pump
- Optional Remote Operation



Model #	Part #	Cabinet	GPM	PSI	Pump RPM	Pump	Motor HP	Volts	Phase	Amps	Ship Wt (lbs)
SEA3-11024D	1.106-500.0	SS	2.8	1000	1540	LB3030R	2.0	120	1	20	210
SEA4-20024A	1.106-501.0	SS	4.2	2000	1013	LT6036R.2	6.2	230	1	28	280
SEA4-20024B	1.106-502.0	SS	4.2	2000	1013	LT6036R.2	6.2	230	3	16	220
SEA4-20024C	1.106-503.0	SS	4.2	2000	1013	LT6036R.2	6.2	460	3	7.2	220
SEA4-20024G	1.106-505.0	SS	4.2	2000	997	LT6036R.2	6.2	208	1	30	297
SEA4-20024H	1.106-506.0	SS	4.2	2000	1028	LT6036R.2	6.2	208	3	18.5	220
SEA4-30024B	1.106-507.0	SS	3.5	3000	943	LT6036R.2	7.5	230	3	21.5	235
SEA4-30024C	1.106-508.0	SS	3.5	3000	943	LT6036R.2	7.5	460	3	10.5	305
SEA3-11024D	1.106-583.0	MS	2.8	1000	1500	LB3030R	2.0	120	1	20	275
SEA4-20024A	1.106-584.0	MS	4.2	2000	1281	LM4035R.3	6.2	230	1	29	275
SEA4-20024B	1.106-585.0	MS	4.2	2000	1281	LM4035R.3	6.2	230	3	11	275
SEA4-20024C	1.106-586.0	MS	4.2	2000	1281	LM4035R.3	6.2	460	3	11	275
SEA4-20024H	1.106-587.0	MS	4.2	2000	1281	LM4035R.3	6.2	208	3	16	275
SEA4-30024B	1.106-588.0	MS	3.5	3000	1070	LM4035R.3	7.5	230	3	19	275
SEA4-30024C	1.106-589.0	MS	3.5	3000	1070	LM4035R.3	7.5	460	3	11	275

Dimensions: 31"L x 21"W x 16"H

Field Installed Options & Accessories

- 9.801-036.0 Cox Hose Reel Kit (floor stand / wall mount)
- 8.903-521.0 E-Zee Hose Reel & Mounting Kit
- 9.802-265.0 Hose Reel, Mini, (fits wall bracket, 150' capacity)
- 8.711-860.0 Hose Reel, Mini, (fits wall bracket, 100' capacity)
- 8.903-040.0 24" Floor Stand
- 9.801-035.0 Wheel Kit (4 casters) for Floor Stands
- 9.801-031.0 Wheel Kit with Detergent Rack
- 9.801-034.0 36" Floor Stand
- 8.903-617.0 36" Floor Stand (stainless steel)

Mild Steel Models Only

- 8.903-045.0 Time Delay Shutdown Kit 120v 1ph ♦
- 8.929-374.0 Time Delay Shutdown Kit 208/230v 1ph ♦
- 8.903-041.0 Time Delay Shutdown Kit 3ph ♦
- 8.929-376.0 Auto start/Stop Kit 120v 1ph ♦
- 8.929-377.0 Auto Start/Stop Kit 208/230v 1ph ♦
- 8.903-047.0 Auto Start/Stop Kit 3ph ♦
- 9.801-033.0 Wall Mount Bracket Assembly

Field Installed Options & Accessories

Stainless Steel Models Only

- 8.929-497.0 LanCom Kit 1-step 460V 3 ph ♦ ◊ ■
- 8.929-498.0 LanCom Kit 2-step 460V 3 ph ♦ ◊ ■
- 8.930-163.0 LanCom Kit 1-step 208/230V 3ph ♦ ◊ ■
- 8.930-177.0 LanCom Kit 2 step 208/230V 3ph ♦ ◊ ■
- 8.929-382.0 LanCom Kit 1-step 208/230v 1 ph ♦ ◊ ■
- 8.929-383.0 LanCom Kit 2-step 208/230v 1ph ♦ ◊ ■
- 8.903-461.0 Remote On/Off Switch Option (Time Delay units only) ♦ •
- 8.930-358.0 Additional LanCom Remote
- 8.903-619.0 Wall Mount Bracket Assembly
- 8.903-511.0 Auto Start/Stop Kit 208/230/460v 3ph ♦
- 8.929-380.0 Auto Start/Stop Kit 120v 1ph ♦
- 8.929-381.0 Auto Start/Stop Kit 208/230 1ph ♦
- 8.904-527.0 Wheel Kit with Detergent Rack (stainless steel)
- 8.903-448.0 Float Tank Option with Inlet Soap Injection ♦ •

- ♦ Factory Installed
- Not compatible with LanCom ◊ Not compatible with Float Tank options
- Not available on stainless steel model SEA3-11024D