

# SLT



## Hot Water Diesel or Gas Powered Diesel/Oil Heated

The SLT is a beast and is the go-to pressure washer for many workers in the mining, drilling and fleet industries. It has no problem taking on stubborn grime and grease. With its most powerful model reaching cleaning conditions of up to 8.0 GPM and 3200 PSI, the SLT has the ability to reach hot water temperatures of up to 200°F. Its unique stainless steel coil top wrap offers protection, while its oversize vibration isolators help to cushion the engine and pump platform. With extra-large heating coils and fuel tanks, there's no wonder why the SLT is the preferred cleaning machine by so many industrial professionals.

- Up to 8.0 GPM / 3,200 PSI
- Belt-Drive Pump
- Diesel or Gas Engine
- Multi-User Operation
- Rugged Steel Skid Frame



Model #	Part #	GPM	PSI	Pump RPM	Pump	Engine	CCs	Engine Fuel	Ship Wt (lbs)
SLT6-32324E	1.110-520.0	5.9	3200	1570	LT6036L.2	Honda GX630	688	Gasoline	1245
SLT8-30324E	1.110-522.0	7.8	3000	1470	LX9536L.2	Honda GX690	688	Gasoline	1230
SLT6-32624E	1.110-065.0	6.25	3200	1625	LT6036L.2	Kubota D1105	1123	Diesel	1745
SLT8-32624E	1.110-066.0	8.0	3200	1450	LX9536L.2	Kubota D1105	1123	Diesel	1811

Dimensions: SLT6/SLT8 Gasoline 55"L x 32"W x 51"H SLT6/SLT8 Diesel 62"L x 32"W x 57"H  
E = Electric start engine (battery not included)

### Field Installed Options & Accessories

8.920-751.0	Float Tank w/ Inlet Chemical Injection
8.904-456.0	Downstream Injector
8.920-977.0	Steam Valve

