

# 30-Gallon | Two Stage Diesel



Designed for optimum performance and productivity, the diesel 30-gallon air compressor features a large-capacity ASME coded tank and two stage, cast iron compressor pump. This high-powered unit supplies consistent air flow required for commercial and industrial applications.



### Compressor Pump

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

### Engine

- Electric start - battery, box and cables not included
- Glow plug equipped engine for easy starting in cold temperatures

### Frame

- Powder coated ASME coded 30-gallon receiver tank
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Removable base plate offers flexible installation

### Components

- Regulator and two gauges for tank and outlet pressure
- ASME safety valves
- Tank drain valve

ABS-9KD-30H



Model Number	CFM @ PSI	Horsepower/Engine	Compressor	Engine Idle Control	Dimensions (LxWxH)	Ship Wt.	Net Wt.
ABS-9KD-30H	29.0 @ 175*	9.1 HP Kohler KD440 OHV	Two stage, cast iron	Cable throttle	38x23x46.5in.	540 lb.	483 lb.

\*Equipped with 150-PSI maximum rated regulator.

Accessory & Option:		
Part Number	Description	Fits Model
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new	ABS-9KD-30H
IX-0001	Vibration isolator pads - Isolators protect the unit from vibration during use; Recommended for models that are mounted in service truck applications	ABS-9KD-30H