

8-Gallon | Two Stage Gasoline



Designed with both contractors and remodelers in mind, the 8-gallon two stage air compressor is perfect for job site tasks requiring a higher CFM and air pressure.



Compressor Pump

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Frame

- Powder coated 8-gallon twin tank receivers
- 3/16-inch base plate to reduce vibration
- 14-gauge powder coated two-piece belt guard
- Flat-free tires

Components

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16 1/2-inch fly wheel
- Quality pilot valve unloader

AM2-PH09-08M

Model Number	CFM @ PSI*	Displacement/Engine	Compressor	Tank Size	Engine Idle Control	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AM2-PH09-08M	17.2 @ 175	270cc Honda GX270 OHV	Two stage, cast iron	8-gallon	Pneumatic	44x26x31in.	330 lb.	260 lb.
AM2-PK95-08M	17.2 @ 175	277cc Kohler CH395 OHV	Two stage, cast iron	8-gallon	Cable throttle	44x26x31in.	330 lb.	260 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

Part Number	Description	Fits Models
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new	All models
AX-0003	Manual drain/regulator/metal bowl - Drains moisture from air system	All models
AX-0015	Electric start - battery and cables not included - For easy starting	AM2-PH09-08M
IX-0055	Remote start/choke - 6-ft. wire extension for key switch; you will also need to order AX-0015	AM2-PH09-08M