



30-Gallon | Two Stage Diesel

The 30-gallon diesel air compressor/generator is perfect for agricultural, construction and industrial applications that require both electrical power and compressed air.



AG2-SKD9-30M



Compressor Pump

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Generator

- Brushless alternator
- Total harmonic distortion (THD) less than 6%
- 100% copper windings
- Comes standard with (2) 120V, 20A and (1) 240V, 20A receptacles

Engine

- Electric start - battery, box and cables not included
- Glow plug equipped engine for easy starting in cold temperatures

Frame

- Powder coated ASME coded 30-gallon receiver tank
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard

Components

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16 1/2-inch fly wheel
- Quality pilot valve unloader

Model Number	CFM @ 90 PSI	CFM @ 175 PSI*	Max. Output	Alternator Wattage		Receptacles	Horsepower/Engine	Compressor	Dimensions (LxWxH)	Ship Wt.	Net Wt.
				Cont. With Comp. On-Load	Cont. With Comp. Off-Load						
AG2-SKD9-30M	16.4	15.7	3000 watts	2300 watts	2750 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	9.1 HP Kohler KD440 OHV	Two stage, cast iron	41x23x47in.	554 lb.	489 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:		
Part Number	Description	Fits Model
70-0380	Engine oil drain extension - 14-inch flexible drain hose makes oil changes clean and easy	AG2-SKD9-30M
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new	AG2-SKD9-30M
IX-0001	Vibration isolator pads - Isolators protect the unit from vibration during use; Recommended for models that are mounted in service truck applications	AG2-SKD9-30M