



PRODUCT PROFILE

INDUSTRIAL DETERGENTS

CHAMPION™

FORMULA 226

Heavy Duty Floor Cleaner & Degreaser



DESCRIPTION

Champion™ is a heavy duty powdered steam cleaning compound which cleans quickly, effectively and will not clog lines or corrode equipment. It removes heavily encrusted grease and soil by its outstanding cleaning power which is accomplished by a special blend of emulsifiers and not a high caustic content. Champion's™ uses vary from cleaning transportation vehicles to cleaning concrete floors in mechanic shops. This formula meets USDA requirements is an ideal powder for meat and poultry processors

AT A GLANCE



- *Excellent Concrete Cleaner*
- *Quickly removes encrusted grime*
- *Meets USDA Requirements*

APPLICATIONS

Cleaning Concrete Floors	Gas Islands	Garages
Mechanic Shops	Meat and Poultry Processing Plants	Drive ways & side walks

SPECIFICATIONS

Physical Form: Powder	pH (1% dilution): 11.0 - 12.0
Recommended Dilution: Varies - See Label	DOT Class: Corrosive
Color: Orange	Fragrance: None

PRODUCT AVAILABILITY

Available Sizes	Container Type	Weight per Container	QTY per pallet	Ships UPS	Additional Hazard Fee
40 Lbs.	Round Pail	40 lbs.	20	Yes	Yes



PRODUCT PROFILE

INDUSTRIAL DETERGENTS

FORMULA 226

Sample Label

INDUSTRIAL CLEANING

KO

Corrosive Solids (Sodium Hydroxide), UN 1759.

CHAMPION™

HEAVY DUTY FLOOR CLEANER & DEGREASER

FORMULA 226
NET CONTENT 40 Lbs (18.2 Kg)
100 Lbs (180 Kg)

DESCRIPTION:
• Extra Powerful Cleaner & Degreaser
• Granular Particles Help Penetrate Deep into the Soil Removing Tough Grease, Oil & Grime
• Makes an Exceptional Concrete Cleaner
• Safe in Steam Cleaners

INGREDIENTS:
Contains Sodium Hydroxide, Water Conditioners, 2-Butoxyethanol and a Proprietary Blend of Surfactants.

HAZARD WARNING:
Corrosive Material! Contact with skin and eyes may cause severe burns. Inhalation of mist can cause irritation and burns to nose, throat. Ingestion can cause severe burns to mouth, throat and stomach. When handling, wear safety glasses, rubber gloves, apron and rubber boots.

FIRST AID:
Eyes and Skin: Flush thoroughly with water for 15 minutes and consult a physician immediately. Inhalation: Remove to fresh air. Treat symptomatically. Ingestion: Do not induce vomiting. Dilute by drinking 2 large glasses of water. Get medical attention immediately. Never give anything by mouth to an unconscious person.

ATTENTION: Refer to our MSDS regarding Handling and disposal of this product.

IN CASE OF EMERGENCY: Call Chemtrec, day or night for assistance and information concerning spilled material, fire, explosion, and other accidents. **1-800-424-9300**

Dilutions Chart:

Surface:	General Cleaning:	*Heavy Cleaning:
Painted Aluminum (Vehicles, Boats, Siding)	40:1	8:1
Stone	40:1	8:1
Concrete	40:1	8:1
Stucco	40:1	8:1
Brick	40:1	8:1
Asphalt	8:1	1:1
Roofing	8:1	1:1
FRP Board	40:1	4:1
Treated Outdoor Wood (Decks & Fencing)	8:1	1:1
Ceramic Tile	40:1	8:1
Porcelain	40:1	8:1
Chrome	40:1	8:1
Steel	40:1	8:1
Stainless Steel	40:1	8:1
Plastic	40:1	8:1
Fiber Glass	40:1	8:1
Canvas	40:1	8:1
Carpet	80:1	40:1
Vinyl Tile	40:1	4:1
Rubber	40:1	4:1
Other Painted Surfaces	40:1	4:1

Other Painted Surfaces: 40:1
*For extremely heavy soils, wet surface first, apply Champion™, scrub, necessary & rinse clean.

If in doubt, spot test on hidden surface first. Do not use on leather, suede, untreated wood furniture, plastic vehicle instrument panels, uncoated soft metals, or other non-waterproof surfaces.

KO MANUFACTURING INC., Springfield, Missouri (417) 866-8000
www.komfg.com

RESEARCH

Through R&D and field testing, KO Chemists combine creativity with technology to bring you products with the performance you require. Using our sophisticated KO lab we continually test new products, existing products, and our manufacturing processes for effectiveness and affordability. When a new product meets our requirements, it goes to a select group of end-users for real-world evaluation. Only after testing, evaluating, and re-testing is a KO product ready for distribution.

Dilutions Chart:

Surface:	General Cleaning:	*Heavy Cleaning:
Painted Aluminum (Vehicles, Boats, Siding)	40:1	8:1
Stone	40:1	8:1
Concrete	40:1	8:1
Stucco	40:1	8:1
Brick	40:1	8:1
Asphalt	8:1	1:1
Roofing	8:1	1:1
FRP Board	40:1	4:1
Treated Outdoor Wood (Decks & Fencing)	8:1	1:1
Ceramic Tile	40:1	8:1
Porcelain	40:1	8:1
Chrome	40:1	8:1
Steel	40:1	8:1
Stainless Steel	40:1	8:1
Plastic	40:1	8:1
Fiber Glass	40:1	8:1
Canvas	40:1	8:1
Carpet	80:1	40:1
Vinyl Tile	40:1	4:1
Rubber	40:1	4:1
Other Painted Surfaces	40:1	4:1

Attention: Refer to our Material Safety Data Sheet regarding hazards, personal protection, and disposal of this product.

KEEP IT CLEAN™
KO MANUFACTURING, INC.
2720 E. Division • Springfield, MO 65803

800.777.SOAP
800.777.7627
www.komfg.com