

## DEALER HOT WATER PRESSURE WASHERS

## PORTABLE GASOLINE

DIRECT DRIVE – DHS SERIES



DH-3504-SP3H6A

- Direct drive triplex piston pump with ceramic plungers
- External bypass system protects from heat build-up (AR pump models)
- Preset stainless-steel and brass unloader valve
- Performance-proven engine with low-oil protection
- Electro Magnetic Firing (EMF) system
- Reinforced powder coated steel frame with center balanced lift
- 13-inch flat-free tires
- Top-fired powder coated heat exchanger
- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided high pressure hose with quick connects
- Adjustable pressure insulated dual lance with trigger gun
- 3 year limited Honda, Kohler, Mi-T-M and Vanguard engine warranties
- CSA Certified – US and Canada (Consult factory for models)

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	SHIP WT.	NET WT.
DH-2503-SP0H6M	2500	2.6	196cc Honda GX200 OHV	Mi-T-M	411 lb.	295 lb.
DH-2503-SP0K6M	2500	2.6	208cc Kohler CH270 OHV	Mi-T-M	411 lb.	295 lb.
DH-2503-SP0M6M	2500	2.6	212cc Mi-T-M OHV	Mi-T-M	411 lb.	295 lb.
DH-3003-SP3H6A	3000	2.9	270cc Honda GX270 OHV <sup>+</sup>	AR	530 lb.	407 lb.
DH-3504-SP3H6A	3500	3.3	389cc Honda GX390 OHV <sup>+</sup>	AR	551 lb.	428 lb.
DH-3504-SP3K6A	3500	3.3	429cc Kohler CH440 OHV	AR	551 lb.	428 lb.
DH-3504-SP3M6A	3500	3.3	420cc Mi-T-M OHV	AR	551 lb.	428 lb.
DH-3504-SP3V6A	3500	3.3	408cc Vanguard OHV	AR	551 lb.	428 lb.

<sup>+</sup>49 state engine. Not for sale in California.

## ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector – High pressure water mixes with detergent to clean even the heaviest build-up	All models
850-0433	50-foot x 3/8-inch hose – For when you need extra hose for added mobility	3500-PSI models
851-0262	50-foot x 3/8-inch hose – For when you need extra hose for added mobility	2500 to 3000-PSI models

## OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
HX-0234	Low pressure detergent injector – Allows the user to apply the recommended detergents	2500-PSI models
HX-0274	Rain cap – Protects boiler from moisture build-up when unit is left outside	3000 to 3500-PSI models
HX-0236	Hour meter – Displays the number of hours unit has been in operation	2500-PSI models
HX-0279*	Hour meter – Displays the number of hours unit has been in operation	3000 to 3500-PSI models
HX-0233	Adjustable thermostat – Operator is able to adjust outlet water temperature between 98°-248°F	2500-PSI models
HX-0280*	Adjustable thermostat – Operator is able to adjust outlet water temperature between 98°-248°F	3000 to 3500-PSI models
HX-0281	Hour meter and adjustable thermostat – Displays the number of hours unit has been in operation; operator is able to adjust outlet water temperature between 98°-248°F	3000 to 3500-PSI models
HX-0286	Electric start – battery not included – For easy starting	DH-3504-SP3H6A
HX-0300	Skid feet – For stationary applications	3000 to 3500-PSI models

\*You cannot order HX-0279 and HX-0280 together, you will need to order HX-0281 instead. HX-0279 and HX-0280 can be ordered separately.