

Gas-Fired Convection | 60,000 up to 200,000 BTU

Heat your space quietly and efficiently while providing instant heat without the need of electricity. The gas-fired convection heater is perfect for workshops, construction sites, farm sites and loading docks with proper ventilation.



MH-0200-CM10

Frame

- Quick assembly 2-piece burn chamber
- Durable steel housing
- Inner windshield protects burner flame from being extinguished

Heat Output

- Variable heat settings
- 360-degree heat radius for even heating of room

Components

- Matchless piezo spark ignition
- Automatic shut-off if flame is extinguished

Model Number	MH-0080-CM10	MH-0100-CM1N	MH-0200-CM10
Heat Output	60-80,000 BTU	50-100,000 BTU	50-200,000 BTU
Hot-Air Flow	N/A	400 CFM	N/A
Ignition Type	Automatic (integral)	Control knob ignition	Push-button
Fuel	Propane	Natural Gas	Propane
Fuel Consumption	2.3 / 3.7 lb./hr.	2.13 minimum / 4.63 maximum lb./hr.	3.24 / 9.25 lb./hr.
Operating Time (100 lb. Cyl.)	43 / 27 hours	N/A	31 / 11 hours
Operating Time (40 lb. Cyl.)	17 / 11 hours	N/A	N/A
Operating Time (20 lb. Cyl.)	8 / 5 hours	N/A	N/A
Suggested Cylinder Size	100 lb.	N/A	100 lb.
Inlet Gas Pressure	N/A	7in. WC minimum / 14in. WC maximum	N/A
Heating Area	1,800 sq. ft.	3,000 sq. ft.	4,600 sq. ft.
Stainless-Steel Burner	No	Yes	No
Hose & Regulator	Yes, 10 ft.	No	Yes, 10 ft.
Dimensions (LxWxH)	15.7x15.7x21.8in.	15.7x15.7x26.4in.	16x16x26.4in
Ship Wt.	17 lb.	21 lb.	20 lb.
Net Wt.	11.5 lb.	14.3 lb.	14 lb.

Important Notes

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Extremely hot during operation. Keep children, animals and all combustible objects away from heater.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances.

Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.



Accessory		
Part Number	Description	Fits Models
68-5010	Two cylinder manifold - Connects any two propane cylinders	All models