# Kerosene Forced Air | 75,000 up to 600,000 BTU

The kerosene-fired forced air heaters are portable and easy to operate. Extend heat into wide areas creating a comfortable work environment even in the harshest conditions. For use in farms, workshops, warehouses, garages and construction sites with proper ventilation.





Motor

- Heavy-duty, high quality cast aluminum enclosed electric motor

#### **Burner Head**

- 1-piece cast aluminum

#### Components

- High performance fan
- Built-in temperature control thermostat with control dial
- Integral overheat and flame-out safety
- Fuel gauge
- Sure start ignition for cold temperature starts
- Dual connector ignition

## **Factory Tested for Multiple Fuels**

- Kerosene
- JP8/Jet A fuel
- No. 1 and No. 2 fuel oil
- No. 1 and No. 2 diesel fuel

### **Important Notes**

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Must be plugged into an approved standard electrical outlet for operation

MH-0190-0M10



CSA CERTIFIED

Model Number	MH-0075-0M10	MH-0135-0M10	MH-0190-0M10	MH-0215-0M10	MH-0400-0M10	MH-0600-0M10
Heat Output	75,000 BTU	135,000 BTU	190,000 BTU	215,000 BTU	400,000 BTU	600,000 BTU
Hot-Air Flow	240 CFM	540 CFM	630 CFM	670 CFM	1,400 CFM	3,000 CFM
Air Pump Pressure	4.0 PSI	5.0 PSI	7.5 PSI	9.0 PSI	125 PSI	128 PSI
AC Power	12V, 60Hz, 1.5 Amps	120V, 60Hz, 2.3 Amps	120V, 60Hz, 2.7 Amps	120V, 60Hz, 2.8 Amps	120V, 60Hz, 3.0 Amps	120V, 60Hz, 5.5 Amps
Motor Size	1/8 HP	1/5 HP	1/4 HP	1/3 HP	1/2 HP	5/8 HP
Fuel Tank Capacity	5.0 gallons	10.0 gallons	13.0 gallons	13.0 gallons	24.0 gallons	40.0 gallons
Fuel Consumption	0.56 gal./hr.	1.00 gal./hr.	1.42 gal./hr.	1.63 gal./hr.	3.00 gal./hr.	4.50 gal./hr.
Max. Operating Hours	8.9 hours	10.0 hours	9.1 hours	8.0 hours	8.0 hours	8.9 hours
Heating Area	1,700 sq. ft.	3,100 sq. ft.	4,300 sq. ft.	5,300 sq. ft.	10,000 sq. ft.	15,000 sq. ft.
Multi-Fuel Capable	Yes	Yes	Yes	Yes	Yes	Yes
Digital Temp. Read-Out	No	Yes	Yes	Yes	No	No
Error Indicator Read-Out	No	Yes	Yes	Yes	Yes	Yes
Parts Storage System	No	Yes	Yes	Yes	Yes	Yes
Dimensions (LxWxH)	30x13x15in.	37x22x25in.	42x24x26in.	42x24x26in.	53x30x36in.	75x34x43in.
Ship Wt.	33 lb.	57 lb.	65 lb.	68 lb.	159 lb.	376 lb.
Net Wt.	28 lb.	51 lb.	58 lb.	61 lb.	150 lb.	320 lb.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances.

Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.