



**Hanson**  
Industrial - Peoria, Inc.

# Premium Series

Dealer Cold Water  
Pressure Washers

*Electric — Portable — Belt Drive*



DC-4004-W1E3G shown with 460V, 3-phase motor option, CX-0057

*With up to 5000-PSI of cleaning power, this series of pressure washers is perfect for cleaning heavily soiled equipment, greasy floors and dirty concrete walls.*

**Pump:**

Belt drive triplex piston General pump with ceramic plungers | External bypass system allows more water into the system to protect from heat build-up | Forged brass manifold | Thermal relief valve | Water filter with clear sleeve for screen inspection

**Frame:**

Powder coated steel frame and base plate with 1¼-inch tube handles | Totally enclosed powder coated steel belt guard | 13-inch flat-free tires

**Motor:**

Totally enclosed fan-cooled electric motor with thermal overload protection | 10-foot power cord

**Component:**

Heavy-duty dual cogged belt drive system

**Unit Includes:**

Quick connect nozzles - 0°, 15°, 25° and 40° | 50-foot x ¾-inch non-marking high pressure hose | 36-inch lance with rubber grip (48-inch on 4000 and 5000-PSI models) | Professional-grade insulated trigger gun with safety lock-off



# Premium Series

## Cold Water – Electric – Portable – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	UNLOADER	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-2405-W4E2G	2400	4.6	7.5 HP, 230V, 1Ø, 32.0A	Factory preset	NEMA 6-50P	46x28x30in.	345 lb.	333 lb.
DC-2405-W4E3G*	2400	4.6	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	Factory preset	NEMA L15-30P	45.5x32.5x30in.	355 lb.	343 lb.
DC-3004-W4E2G	3000	3.5	7.5 HP, 230V, 1Ø, 32.0A	Factory preset	NEMA 6-50P	46x28x30in.	350 lb.	338 lb.
DC-3004-W4E3G*	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	Factory preset	NEMA L15-30P	45.5x32.5x30in.	403 lb.	301 lb.
DC-3005-W0E2G	3000	4.8	10.0 HP, 230V 1Ø, 41.5A	Factory preset	NEMA 6-50P	45.5x32.5x30in.	470 lb.	396 lb.
DC-3005-W0E3G*	3000	4.8	10.0 HP, 230V, 3Ø, 26.0A or 10.0 HP, 460V, 3Ø, 13.0A	Factory preset	NEMA L15-50P	45.5x32.5x30in.	450 lb.	376 lb.
DC-4004-W1E3G*	4000	3.9	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	Factory preset	NEMA L15-50P	45.5x32.5x30in.	505 lb.	431 lb.
DC-5004-W0E3G*	5000	4.0	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	Factory preset	NEMA L15-50P	45.5x32.5x30in.	505 lb.	431 lb.

\*460V motors available as options

### Options:

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0003	460V on 8.0-HP, 3-phase models - For when you have 460V of power available	DC-2405-W4E3G & DC-3004-W4E3G
CX-0005	36-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	DC-2405, DC-3004 & DC-3005 models
CX-0057	460V on 15.0-HP, 3-phase models - For when you have 460V of power available	DC-4004-W1E3G & DC-5004-W0E3G
CX-0062	460V on 10.0-HP, 3-phase models - For when you have 460V of power available	DC-3005-W0E3G
CX-0093	Stationary option - This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	DC-2405 & DC-3004 models
CX-0094	Stationary option - This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	DC-3005, DC-4004 & DC-5004 models

### Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up	All models
851-0317	50-ft. x 3/8-in. non-marking high pressure hose - For when you need extra hose for added mobility	DC-5004-W0E3G
851-0338	50-ft. x 3/8-in. non-marking high pressure hose - For when you need extra hose for added mobility	2400 to 4000-PSI models
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents	All models



NEMA 6-50P,  
50-amp plug



NEMA L15-30P,  
30-amp plug



NEMA 15-50P,  
50-amp plug



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).