

# Propane Tank-Top Radiant | 9,000 up to 32,000 BTU

The propane tank-top radiant heater is convenient, versatile and great for outdoor use. Simply connect to a standard 20 pound propane cylinder and heat your workspace for up to 48 hours. For use in open workshops, construction sites, farms and any other outdoor heating need.



MH-0030-IM10

**Frame**

- Heavy-duty construction
- Rust-proof chrome emitter guard
- Rear burner safety guard

**Heat Output**

- Variable heat control valve
- Clean, quiet, instant radiant heat

**Components**

- Standard propane tank connection
- High efficiency heat reflector
- Hand wheel valve connection

Model Number	MH-0015-IM10	MH-0030-IM10
Heat Output (Single Burner)*	L-9,000 / M-12,000 / H-16,000 BTU	L-9,000 / M-12,000 / H-16,000 BTU
Heat Output (Double Burner)*	N/A	L-18,000 / M-24,000 / H-32,000 BTU
Ignition Type	Match light	Match light
Heat Settings	3	6
Propane Cylinder Size	20 lb.	20 lb.
Max. Operating Hours (20 lb. Cyl.)*	L-48 / M-36 / H-27 hours	L-48 / M-18 / H-14 hours
Swivel Burner Head	No	Yes
Safety Shut-Off Valve	Yes	Yes
Heat Regulator Knob	Yes	Yes
Manifold	Cast aluminum	Cast aluminum
Dimensions (LxWxH)	8.4x7.4x12in.	17.5x5.5x12in.
Ship Wt.	3 lb.	6 lb.
Net Wt.	2 lb.	5 lb.

\*Heat output and operating hours have Low, Medium and High settings.

**Important Notes**

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances.

Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

