

## TULE SERIES HDS 3.5/40 GE MT



Shown with optional hose reel

### Towable and maneuverable hot water pressure washer.

Ready to pick up and go at a moments notice, Kärcher's Tule Series HDS 3.5/40 Ge MT hot water pressure washer trailer provides the necessary cleaning power on virtually any job site which has a water source. Simply unhitch the Tule Series HDS 3.5/40 Ge MT and take the cleaning power where you need it most. The Tule Series trailer features a reliable Honda engine, 8 gallon diesel fuel tank, electric start with manual start backup and much more.

U.S. Design Patent No. 9,724,734 B2



POWERED by  
**HONDA**



### Features

- Honda GX 390 engine and electric start with manual start backup
- Adjustable thermostat for water temperature regulation
- 8 gallon diesel fuel tank
- Lift handle and swing away tongue for easier hook up of the trailer and storage

### TECHNICAL DATA

Model	Part No.	GPM	PSI	Drive	Engine	Start	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) Inches
HDS 3.5/40 Ge MT	1.103-844.0	3.5	4000	Direct	Honda GX390	Electric	Kärcher KS	750	100 x 45 x 75
HDS 3.5/40 Ge MT	1.110-118.0	3.5	4000	Direct	Vanguard 400	Electric	Kärcher KS	750	100 x 45 x 75

### ACCESSORIES

Order No.	Description
■ 8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.
■ 8.756-797.0	3-5 GPM Chemical Injector Kit
■ 8.754-990.0	12V Battery (required for hot water operation)
■ 8.711-293.0	Zinc plated variable pressure lance
■ 8.925-182.0	50', 3/8" hose, double-wire at 6000 PSI

### OPTIONS (FACTORY INSTALLED)

Order No.	Description
<input type="checkbox"/> 8.924-367.0	2-5/16" Ball Coupler
<input type="checkbox"/> 8.924-667.0	Lifting Kit
<input type="checkbox"/> 8.924-370.0	LED Lights
<input type="checkbox"/> 8.924-700.0	2-inch Collar Lock Coupler
<input type="checkbox"/> 8.924-368.0	3" Lunette coupler

### OPTIONS (FIELD INSTALLED)

Order No.	Description
<input type="checkbox"/> 8.750-682.0	Hose Reel Fixed 100', 5000 PSI, 325° F, equipped for 3/8" hose
<input type="checkbox"/> 8.925-255.0	Hose Reel Bracket (Mount Kit)
■ Included <input type="checkbox"/> Optional ■	Please Note: NOT compatible with EASY!Lock