

## DEALER HOT WATER PRESSURE WASHERS

PORTABLE ELECTRIC  
BELT DRIVE – DHS SERIES

DH-2504-SE0E3G

- Belt drive triplex piston pump with ceramic plungers
- External bypass system protects from heat build-up
- Factory preset unloader
- Totally enclosed fan-cooled electric motor
- 35-foot power cord
- Energy-efficient top-fired heat exchanger
- Reinforced powder coated steel frame with center balanced lift
- 13-inch flat-free tires
- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/4-inch steel wire-braided high pressure hose with quick connects
- Adjustable pressure insulated dual lance with trigger gun
- 1 year limited electric motor warranty
- Intertek Certified – US and Canada

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	SHIP WT.	NET WT.
DH-2504-SE0E2G	2500	3.2	6.0 HP, 230V, 1Ø, 25.0A	General	699 lb.	569 lb.
DH-2504-SE0E3G	2500	3.2	6.0 HP, 230-460V, 3Ø, 16.0A	General	688 lb.	558 lb.
DH-3004-SE0E2G	3000	3.5	8.0 HP, 230V, 1Ø, 36.0A	General	737 lb.	607 lb.
DH-3004-SE0E3G	3000	3.5	8.0 HP, 230-460V, 3Ø, 24.0A	General	732 lb.	602 lb.
DH-3504-SE0E2G	3500	3.3	10.0 HP, 230V, 1Ø, 39.0A	General	761 lb.	631 lb.
DH-3504-SE0E3G	3500	3.3	10.0 HP, 230-460V, 3Ø, 28.0A	General	742 lb.	612 lb.

## ACCESSORY:

PART NUMBER	DESCRIPTION	FITS MODELS
850-0433	50-foot x 3/4-inch hose – For when you need extra hose for added mobility	All models

## OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
HX-0070	<b>Auto start/stop</b> – When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	All models
HX-0071	<b>Auto start/stop - steam</b> – When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-2504 models
HX-0072	<b>Auto start/stop - steam</b> – See HX-0071 for description	DH-3004 models
HX-0073	<b>Auto start/stop - steam</b> – See HX-0071 for description	DH-3504 models
HX-0074	<b>Auto start/stop - CAD cell</b> – When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; monitors burner for proper ignition	All models
HX-0075	<b>Auto start/stop - steam - CAD cell</b> – When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F; monitors burner for proper ignition; includes adjustable thermostat	DH-2504 models
HX-0076	<b>Auto start/stop - steam - CAD cell</b> – See HX-0075 for description	DH-3004 models
HX-0077	<b>Auto start/stop - steam - CAD cell</b> – See HX-0075 for description	DH-3504 models
HX-0085	<b>460V on 6.0-HP, 3Ø model</b> – Upgrades 230V, 3Ø model to operate at 460V, 3Ø	DH-2504-SE0E3G
HX-0086	<b>460V on 8.0-HP, 3Ø model</b> – Upgrades 230V, 3Ø model to operate at 460V, 3Ø	DH-3004-SE0E3G
HX-0087	<b>460V on 10.0-HP, 3Ø model</b> – Upgrades 230V, 3Ø model to operate at 460V, 3Ø	DH-3504-SE0E3G
HX-0088	<b>Skid feet</b> – Stationary applications	All models
HX-0161	<b>Hour meter</b> – Displays the number of hour unit has been in operation	All models
HX-0294	<b>Adjustable thermostat</b> – Operator is able to adjust outlet water temperature between 86°-248°F	All models