From The Forest Engineered Hardwood Flooring

Woodland Treasures Collection:

- Wide plank (7.5") flooring (Reduced install time and minimizes seams to create a larger room appearance)
- 4mm White Oak Veneer/Wear-layer (Allows for the product to be sanded and refinished up to 3x)
- 11.2mm thick 9-ply hardwood core (Uniform durability throughout)
- UV-Cured Stains (Fade-, UV-, Resistant)
- UV-cured WearMax™ DWR Topcoat (No off-gassing of harmful chemicals and Resistance to dents, scratches and water)
- Standard Tongue & Groove Interlocking System (industry-proven quality and versatility)
- Low-gloss (perfect for installation areas of any lighting types or degrees)
- Wire-brushed Veneer texture (creates natural feel of wood and provides additional grip to better limit slips and falls)
- Character/Natural Grade (presents the most authentic and natural wood look, without discounting durability)
- Installation Grade: above grade, on grade, and below grade
- Installation Method(s): Glue down, Nail down, Staple Down, or Free-float(w/ or w/o underlayment)
- Compatible Subfloor Types: Plywood, OSB, Concrete, Radiant heat subfloor w/plywood, Existing Hardwood Flooring, Existing Tile, and more.

Naturals Collection:

- 5" wide micro-beveled plank flooring (common to industry and easy to manage for DIY-projects)
- 3mm Red Oak, Maple or Hickory Veneer/Wear-layer (Allows for the product to be sanded and refinished 2x)
- 9mm thick 7-ply hardwood core (Uniform durability throughout)
- UV-Cured Stains (Fade-; UV-Resistant)
- UV-cured WearMax™ DWR Topcoat (No off-gassing of harmful chemicals and Resistance to dents, scratches and water)
- Standard Tongue & Groove Interlocking System (industry-proven quality and versatility)
- Medium-gloss (perfect for installation areas of any lighting types and brightens up lowerlit areas)
- Smooth Veneer texture (creates natural feel of wood and provides additional grip to better limit slips and falls)
- Character/Natural Grade (presents the most authentic and natural wood look, without discounting durability)

- Installation Grade: above grade, on grade, and below grade
- Installation Method(s): Glue down, Nail down, Staple Down, or Free-float(w/ or w/o underlayment)
- Compatible Subfloor Types: Plywood, OSB, Concrete, Radiant heat subfloor w/plywood, Existing Hardwood Flooring, Existing Tile, and more.

Choice Collection:

- Wide plank (7.5") flooring (Reduced install time and minimizes seams to create a larger room appearance)
- 2mm White Oak or Hickory Veneer/Wear-layer (Allows for the product to be sanded and refinished 1x)
- 9mm thick 7-ply hardwood core (Uniform durability throughout)
- Water-based Stains (Fade-; UV-Resistant)
- UV-cure Topcoat (No off-gassing of harmful chemicals and Resistance to dents, scratches and water)
- Standard Tongue & Groove Interlocking System (industry-proven quality and versatility)
- Low-gloss (perfect for installation areas of any lighting types or degrees)
- Wire-brushed Veneer texture (creates natural feel of wood and provides additional grip to better limit slips and falls)
- Character/Natural Grade (presents the most authentic and natural wood look, without discounting durability)
- Installation Grade: above grade, on grade, and below grade
- Installation Method(s): Glue down, Nail down, Staple Down, or Free-float(w/ or w/o underlayment)
- Compatible Subfloor Types: Plywood, OSB, Concrete, Radiant heat subfloor w/plywood, Existing Hardwood Flooring, Existing Tile, and more.

Anchor Click & Lock Collection:

- 5" wide plank flooring (common to industry and easy to manage for DIY-projects)
- Nominal 1mm White Oak Veneer/Wear-layer
- 7.4mm thick HDF core (High density fiberboard to provide superior compact durability with recycled wood fibers)
- Water-based Stains (Fade-; UV-Resistant)
- UV-cure Topcoat (No off-gassing of harmful chemicals and Resistance to dents, scratches and water)
- Revolutionary click & lock Interlocking system (allows for quick and easy installation with more secure fit)
- Low-gloss (perfect for installation areas of any lighting types or degrees)
- Wire-brushed Veneer texture (creates natural feel of wood and provides additional grip to better limit slips and falls)

- Select and Better Grade (presents clean wood look with its uniform grain texture and mild color variations)
- Installation Grade: above grade, on grade, and below grade
- Installation Method(s): Glue down, Nail down, Staple Down, or Free Float using click & lock system (w/ or w/o underlayment)
- Compatible Subfloor Types: Plywood, OSB, Concrete, Radiant heat subfloor w/plywood, Existing Hardwood Flooring, Existing Tile.

Anchor Click & Lock Collection w/VacuuBond™:

- 5" wide plank flooring (common to industry and easy to manage for DIY-projects)
- Nominal 1mm White Oak Veneer/Wear-layer
- 7.4mm thick HDF core (High density fiberboard to provide superior compact durability with recycled wood fibers)
- Water-based Stains (Fade-; UV-Resistant)
- UV-cure Topcoat (No off-gassing of harmful chemicals and Resistance to dents, scratches and water)
- Revolutionary click & lock Interlocking system (allows for quick and easy installation with more secure fit)
- Low-gloss (perfect for installation areas of any lighting types or degrees)
- Wire-brushed Veneer texture (creates natural feel of wood and provides additional grip to better limit slips and falls)
- Select and Better Grade (presents clean wood look with its uniform grain texture and mild color variations)
- Installation Grade: above grade, on grade, and below grade
- Installation Method(s): pre-applied VacuuBond™ adhesive (Nail down/Staple down if needed)
- Compatible Subfloor Types: Plywood, OSB, Concrete, Existing Hardwood Flooring, Existing Tile.

Vineyard Pinot Collection:

- 5" wide plank flooring (common to industry and easy to manage for DIY-projects)
- Nominal 1mm White Oak Veneer/Wear-layer
- 7.4mm thick HDF core (High density fiberboard to provide superior compact durability with recycled wood fibers)
- Water-based Stains (Fade-; UV-Resistant)
- UV-cure Topcoat (No off-gassing of harmful chemicals and Resistance to dents, scratches and water)
- Standard Tongue & Groove Interlocking System (industry-proven quality and versatility)
- Low-gloss (perfect for installation areas of any lighting types or degrees)

- Wire-brushed Veneer texture (creates natural feel of wood and provides additional grip to better limit slips and falls)
- Character/Natural Grade (presents the most authentic and natural wood look, without discounting durability)
- Installation Grade: above grade, on grade, and below grade
- Installation Method(s): Glue down, Nail down, Staple Down, or Free-float(w/ or w/o underlayment)
- Compatible Subfloor Types: Plywood, OSB, Concrete, Radiant heat subfloor w/plywood, Existing Hardwood Flooring, Existing Tile.

RWP w/VacuuBond™ Collection:

- Wide plank (6.65") flooring (Reduced install time and minimizes seams to create a larger room appearance)
- 2mm White Oak or Maple Veneer/Wear-layer
- 3-ply 2mm veneer construction (Even durability throughout the product)
- Water-based Stains (Fade-; UV-Resistant)
- Commercial-rated UV-cure Topcoat (No off-gassing of harmful chemicals and Resistance to dents, scratches and water)
- Standard Tongue & Groove Interlocking System (industry-proven quality and versatility)
- Low-gloss (perfect for installation areas of any lighting types or degrees)
- Smooth Veneer texture (creates natural feel of wood and provides additional grip to better limit slips and falls)
- Character/Natural Grade (presents the most authentic and natural wood look, without discounting durability)
- Installation Grade: above grade, on grade, and below grade
- Installation Method(s): pre-applied VacuuBond™ adhesive (Nail down/Staple down if needed)
- Compatible Subfloor Types: Plywood, OSB, Concrete, Radiant heat subfloor w/plywood, Existing Hardwood Flooring, Existing Tile.

Highland Pro Collection:

- 3.25" wide plank flooring (common to industry and easy to manage for DIY-projects)
- Solid Red Oak or Hard Maple Planks (Uniform durability that fully captures the both the look and feel of that wood species)
- Solid-wood product (Even durability throughout the product with the most natural wood floor feel)
- Water-based Stains (Fade-; UV-Resistant)
- Commercial-rated UV-cure Topcoat (No off-gassing of harmful chemicals and Resistance to dents, scratches and water)
- Standard Tongue & Groove Interlocking System (industry-proven quality and versatility)

- Medium-gloss (perfect for installation areas of any lighting types and brightens up lower-lit areas)
- Smooth facial texture (creates natural feel of wood and provides additional grip to better limit slips and falls)
- Select and Better Grade (presents clean wood look with its uniform grain texture and mild color variations)
- Installation Grade: above grade, on grade, and below grade
- Installation Method(s): Glue down, Nail down, Staple Down, or Free-float (w/ or w/o underlayment)
- Compatible Subfloor Types: Plywood, OSB, Concrete, Radiant heat subfloor w/plywood, Existing Hardwood Flooring, Existing Tile.

icickness stant? Plywood, OSB, Concrete, Plywood, OSB, Concrete, Plywood, OSB, Concrete, Plywood, Dilant? Pes Yes Yes Yes Stant? Yes Yes Stallant? Yes Yes Yes Stant? Yes Yes Yes Stant? Yes Yes Yes Stant? Yes Yes Yes Yes Yes Stant? Yes	Key Traits	Vineyard Collection	Anchor Click & Lock Collection	Anchor Click & Lock Collection w/ VacuuBond™	RWP w/VacuuBond™ Collection	Choice Collection	Naturals Collection	Woodland Treasures Collection	Highland Pro Collection
Teacture, Morie Busheled Wine Busheled Wine Busheled Web Chall Wine Busheled Web Chall	nickness	>1mm		>1mm		2mm	3mm	4mm	N/A (Solid Hardwood)
Secretary Write Studied		No		No	Yes (x1)	1)	Yes (x2)	Yes (x3)	Yes (x10)
Sylantic Comment Character Character		White Oak, Hickory	White Oak	White Oak	White Oak, Maple		Maple, Hickory, Red Oak	White Oak	White Oak, Maple
State 1300 pci 1	3	Low	Low	Low	Low	Low	Medium	Low	Medium
Public P									
Blank 57 38"	/iax)	1360-1820 psi	1360 psi	1360 psi	1360-1450 psi	1360-1820 psi	1290-1820 psi	1360 psi	1290-1450 psi
Prince P		3/8"	3/8"	3/8"	1/4"	1/2"	1/2"		3/4"
Desiry Fiberboard Prign Desiry Fiberboar	l Plank	ប្	<u>2</u>	5"	6.65"	7.5"	Q.		3.25"
Part		48"	48"	48"	48"	72"	72"		78"
1	Core Type	7.4mm HDF (High Desity Fiberboard)		7.4mm HDF (High Desity Fiberboard)	2.1mm Hardwood Veneer(Maple)	9mm Plywood	9mm Plywood	11.2mm Plywood	Solid Product
Bysishari? Wassishari? Ves. Ves. <td>Number of</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>,</td> <td></td> <td></td>	Number of						,		
Property Process Pro	Layers/Plys in	1 (solid Core)	1 (Solid Core)	1 (Solid Core)	1 (Solid Core)	7	7	٥	
Yes Yes	Resistant?	Yes	Yes	Yes	Yes		Yes		Yes
Stant? Yes Y		Yes	Yes	Yes	Yes		Yes		Yes
		Yes	Yes	Yes	Yes	Yes	Yes		Yes
air 2 None None <t< td=""><td>sistant?</td><td>Yes</td><td></td><td>Yes</td><td>Yes</td><td>Yes</td><td>Yes</td><td></td><td>Yes</td></t<>	sistant?	Yes		Yes	Yes	Yes	Yes		Yes
All All	al?	None	None	None	None	None	None		None
All All	for ove-,								
		All	All	All	All	All	All	All	All
### ### ### ### ### ### #### #########	Туре	WearMax (UV-Cured)	WearMax (UV-Cured)	WearMax (UV-Cured)	WearMax (UV-Cured)	WearMax (UV-Cured)	WearMax (UV-Cured)	WearMax (UV-Cured)	WearMax (UV-Cured
king Tongue & Groove Click & Lock Click & Lock Tongue & Groove	Character Grade	#1 Common Charater	0.000	1 - 1 - 1 + 0. Dattas	#1 Common Charater	#1 Common Charater	#1 Common Charater	common Charater	1,1,0,4 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0.
	Interlocking	Too 7110 9. Groove	انامار في الممار	つ!: 1, 0, 1 つい	Tangua 9. Granua	Tangua 9. Granus	יייייייייייייייייייייייייייייייייייייי	Tanama 9. Granus	Tosairo B. Groova
Silue down, Nail down, StrFloat Silue dow			Glue down, Nail down, Staple Down, or Free	Pre-applied adhesive (Nail	Pre-applied adhesive	Glue down, Nail down, Staple Down,	Glue down, Nail down, Staple Down, or Free	Glue down, Nail down, Staple Down,	Glue down, Nail down, Staple Down,
Ves Ves No No Yes	(2)	0.000			100000000000000000000000000000000000000	0.000			
Plywood, OSB, Concrete, Plywood, OSB, Concrete, Radiant Radiant heat subfloor Radiant Plywood, OSB, Concrete, Radiant Plywood, Existing Wplywood,		Yes	Yes	No	NO	Plywood OSB	Yes	Plywood OSB	Plywood OSB
Model in Line 3 submood Frywood, Existing by Wplywood, Exi		Plywood, OSB, Concrete,	Plywood, OSB, Concrete,	District Of Dear Control	Plywood, OSB,	Concrete, Radiant	Plywood, OSB, Concrete,	Concrete, Radiant	Concrete, Radiant
Yes Yes Yes Pending Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes	Compatible Subfloor	w/plywood, Existing Hardwood Flooring	w/plywood, Existing Hardwood Flooring	Existing Hardwood Flooring Existing Tile	Hardwood Flooring, Fxisting Tile	w/plywood, Existing Hardwood Flooring	w/plywood, Existing Hardwood Flooring	w/plywood, Existing Hardwood Flooring	w/plywood, Existing Hardwood Flooring
Mes Yes Yes Pending Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes		Yes	Yes	Yes	Pending	Yes		Yes	Pending
res res <td>_</td> <td>Vor</td> <td>Vor</td> <td>Yor.</td> <td>D 5 5 6 7</td> <td>X or</td> <td>Yor</td> <td>X on</td> <td></td>	_	V or	V or	Yor.	D 5 5 6 7	X or	Yor	X on	
Yes Yes <td></td> <td>Yes</td> <td></td> <td>Yes</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> <td></td> <td>Yes</td>		Yes		Yes	Yes	Yes	Yes		Yes
Yes Yes <td>=</td> <td>Yes</td> <td></td> <td>Yes</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> <td></td> <td>Yes</td>	=	Yes		Yes	Yes	Yes	Yes		Yes
Tes Tes <td>_</td> <td>Vor</td> <td></td> <td>Yor.</td> <td>Kon .</td> <td>X or</td> <td>Yor</td> <td></td> <td></td>	_	V or		Yor.	Kon .	X or	Yor		
Yes Yes <td>ant?</td> <td>Yes</td> <td></td> <td>Yes</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> <td></td> <td>Yes</td>	ant?	Yes		Yes	Yes	Yes	Yes		Yes
Yes Yes Yes Yes Yes Yes		Yes		Yes	Yes	Yes	Yes		Yes
		Voc		Vo.	Voc	Voc	Voc		Vo.