

Safety Data Sheet

7500 WearMax VacuuBond Primer

Date: August 1, 2023

Version: 1

Page 1 of 5

1. Identification of the substance or mixture and of the supplier

Product Number(s)	7500
Product Name(s)	WearMax VacuuBond Primer
Chemical Family	Water based dispersion.
Recommended use	Substrate primer for pressure sensitive adhesive and self adhesive flooring and wall covering products.
Restrictions on use	Use only as directed.
Supplier	Trustor Coatings, LLP
Address	840 S 62 nd Avenue Wausau WI 54401 USA
Contact Number	715 849-2989
24 Hour Emergency Phone	Infotrac (800) 535-5053 International (352) 323-3500 (collect)

2. Hazards identification

GHS Classification	Not classified as a hazardous substance or mixture according to OSHA/GHS regulations.
Symbols	None.
Signal Words	None.
Hazard Statements	None.
Precautionary Statements	
Prevention	P264 - Wash hands thoroughly after handling. P280 - Wear protective gloves and eye or face protection.
Response	P302+352 - IF ON SKIN: Wash with plenty of water. P333+313 - IF SKIN IRRITATION OR RASH OCCURS: Get medical advice/attention. P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313 - IF EYE IRRITATION PERSISTS: Get medical advice/attention.
Storage	
Disposal	Leftover product may be allowed to air dry and landfilled once solid. P501 - Dispose of contents/container in accordance with local, state and federal regulations.

Supplemental Information

3. Composition/information on ingredients

Hazardous Components	CAS #	Weight %
2-butoxyethanol	111-76-2	< 1
triethylene glycol monobutyl ether	143-22-6	< 0.2

4. First aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in recovery

Safety Data Sheet

7500 WearMax VacuuBond Primer

Date: August 1, 2023

Version: 1

Page 2 of 5

	position and seek medical advice.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if irritation persists.
Skin Contact	Wash with soap or mild detergent and plenty of water. Get medical advice/attention if irritation occurs. Take off contaminated clothing and wash before reuse.
Ingestion	Obtain immediate medical attention. Keep at rest. Give nothing by mouth. Only induce vomiting at the instruction of a physician.

5. Fire-fighting measures

Extinguishing Media	SUITABLE: Alcohol resistant foam, CO ₂ , powders, water spray. Combustion is unlikely due to high water content. UNSUITABLE: None known.
Special Protective Equipment for Firefighters	Exposure to decomposition products may cause a health hazard. Use appropriate breathing apparatus. Cool closed containers exposed to fire with water. Do not allow run off from fire fighting to enter drains or watercourses.
Specific hazards and combustion products	None known.

6. Accidental release measures

Steps to be taken if material is released or spilled	Exclude sources of ignition and ventilate the area. Avoid breathing vapors. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials like sand, diatomaceous earth, vermiculite, or earth. Place in container for disposal according to local regulations. Clean up with detergent but do not use solvents. Do not allow into drains or watercourses. If material enters drains or sewers, call local sewer or state authority.
---	---

7. Handling and storage

Handling	Persons with a history of skin sensitization problems should not be employed in any process in which this preparation is used. Use appropriate protective equipment. Do not get in eyes, on skin or on clothing. Remove contaminated clothing and clean before reuse. Destroy any clothing items that cannot be decontaminated. Handle in well ventilated areas. Avoid formation of vapor and mist. Always keep in original, tightly closed containers. Isolate from sources of heat, sparks and open flame. Do not eat, drink, or smoke in the workplace. Wash hands before eating, drinking or smoking.
Storage	Store between 5 and 40 °C. Store in tightly closed containers in a properly vented storage area away from heat, sources of ignition and direct sunlight. Keep in original containers.

8. Exposure controls/personal protection

Exposure limits	2-butoxyethanol TWA 20 ppm - ACGIH PEL 50 ppm 240mg/m ³ - OSHA dipropylene glycol mono methyl ether TWA 100 ppm - ACGIH STEL 150 ppm - ACGIH PEL 100 ppm - OSHA
------------------------	--

Safety Data Sheet

7500 WearMax VacuuBond Primer

Date: August 1, 2023

Version: 1

Page 3 of 5

Engineering measures	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations below applicable exposure limits, suitable respiration protection must be worn. Exposure limits should be monitored using suitable analytical equipment.
Respiratory protection	In situations where misting or flying may occur or exposure limits are otherwise exceeded, NIOSH approved respiratory protection should be worn.
Hand protection	Avoid skin contact. Impervious gloves should be worn for direct contact. Additional protection may be necessary to avoid skin contact including use of long sleeves, apron, face shield, boots, or full body protection.
Eye protection	Safety eye wear designed to protect against splash of liquids. Eye wash stations should be available where eye contact may occur.
Skin protection	Work clothes and closed footwear. Affected parts of the body should be washed with soap and water and rinsed thoroughly after contact.
Other protection	Facilities storing or using this material should be equipped with an eyewash facility and a safety shower.

9. Physical and chemical properties

Appearance	Reddish-brown liquid.
Odor	None or slight solvent-like.
Odor threshold	Not determined.
PH	6.0 - 8.0
Melting/Freezing point	32 F (0 C) (estimated) freeze-thaw stable minimum 5 cycles
Initial boiling point and range	212 F (100 C)
Flash point	>212 F (100 C) does not sustain combustion
Evaporation Rate	Not determined.
Flammability (solid, gas)	Not applicable (liquid.)
Lower explosive limit	Not determined.
Upper explosive limit	Not determined.
Vapor pressure	Not determined.
Vapor density	Not determined.
Relative density	1.018 @ 68 F (20 C)
Solubility	Completely soluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition temperature	Not determined.
Viscosity	~25-35" 6 mm DIN cup @ 77 F (25 C)

10. Stability and reactivity

Reactivity	Polymerization will not occur.
-------------------	--------------------------------

Safety Data Sheet

7500 WearMax VacuuBond Primer

Date: August 1, 2023

Version: 1

Page 4 of 5

Stability	Stable under normal conditions.
Possible hazardous reactions	None known
Conditions to avoid	Exposure to temperatures above 200 F and incompatible materials.
Incompatible materials	Strong acids, strong alkalies, and water reactive materials.
Hazardous decomposition products	None known.

11. Toxicological information

The preparation has not been tested for toxicological effects. It is not classified for acute toxicity based upon component data. Based on known effects of the component materials, the product is classified for human health effects as indicated below.

Likely routes of exposure	Skin, eye, inhalation, ingestion.
Eye contact	May cause eye irritation.
Skin contact	Prolonged or repeated contact with skin or mucous membrane may result in irritation.
Inhalation	Inhalation of aerial droplets, aerosols, or mists may cause irritation. Inhalation hazard is not expected when used as directed.
Ingestion	No known significant effects or critical hazards. May cause irritation to the digestive tract.
Target organ effects	None known.
Chronic effects	None known.
Medical conditions aggravated by exposure	None known.
Acute toxicity values	The product has not been tested. Calculated acute toxicity estimates (ATEs) are below. Oral LD-50: > 2000 mg/kg (calculated) Dermal LD-50: > 2000 mg/kg (calculated) Inhalation LD-50: > 20 ml/l (calculated)
Carcinogenicity status	Not recognized as a carcinogen by the IARC, NTP or OSHA.

12. Ecological information

Eco-toxicity	The product has not been tested. It is not classified for aquatic toxicity based on component materials.
Persistence and degradability	Not determined.
Bioaccumulative potential	Not determined.
Mobility in soil	Not determined.
Other adverse effects	None known.

13. Disposal considerations

Dispose of material in accordance with federal, state and local regulations. Do not allow into drains or watercourses.

14. Transport information

DOT description	Not regulated.
------------------------	----------------

Safety Data Sheet

7500 WearMax VacuuBond Primer

Date: August 1, 2023

Version: 1

Page 5 of 5

15. Regulatory information

Toxic Substances Control Act (TSCA)	All components of this product are included on or exempt from the TSCA inventory.	
SARA Title III Section 302	The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.	
SARA Title III Section 313	The following components are subject to reporting levels established by SARA Title III, Section 313:	
	triethylene glycol monobutyl ether (cas# 143-22-6)	revision date: 8-11-1989
Pennsylvania Right to Know	triethylene glycol monobutyl ether (cas# 143-22-6)	revision date: 8-11-1989
California Proposition 65	This product does not contain any California Proposition 65 components.	
VOC Content	This product contains 39.8 g/L of VOCs (calculated in accordance with ASTM D5201).	
	dipropylene glycol methyl ether (cas# 34590-94-8)	0.255 lb./gal
	triethylene glycol monobutyl ether (cas# 143-22-6)	0.014 lb./gal
	2-butoxyethanol (cas # 111-76-2)	0.064 lb./gal
Other international regulations	All components of this product are listed on or in accordance to: IECSC (China) EINECS (Europe) TSCA (USA)	

16. Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgment of the suitability of this information to ensure proper use and to protect the health and safety of employees. The information in this SDS is meant as a description of the safety requirements of our product; it is not to be considered as a guarantee of the properties of the product. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Trustor Coatings, LLP believes the statements, technical information and recommendations contained herein are reliable. They are given without warranty or guarantee of any kind, expressed or implied.

DATE REVISED: August 1, 2023

PREPARED BY: Eric Anderson