

## Technical Data Sheet

### 7500 WearMax VacuuBond Primer

WearMax Multi-Surface Primer is a waterborne dispersion designed to prime various substrates for application of pressure sensitive adhesives (PSA's) or self adhesive flooring and wall cover products. It is suitable for use over concrete, wood, OSB, gypsum board, stone and quarry tile, existing flooring, and more.

#### Properties:

- Fast dry
- Good adhesion on a variety of substrates
- Tinted for ease of application
- Low VOC

**Surface Prep:** Apply to clean surfaces free of grease, oils, and wax. Excess dust should be swept up or vacuumed. Oily, greasy, or grimy surfaces should be washed with an adequate detergent solution and rinsed with clean water. Surfaces that have been waxed may require use of an appropriate wax stripper for optimal adhesion. Adhesion should be verified before use over an existing floor product as it is impossible to anticipate and test all possible combinations of floor products, coating systems, and maintenance products that may be encountered.

**Recommended Application:** Stir or shake well before use. Apply a single coat with a brush, roller, pad, or T-bar. A second coat may be applied to highly porous surfaces, if desired. Apply only when air, surface, and product temperature are above 50 F (10 C.)

**Dry time:** Dry time will vary with application amount, substrate porosity, ambient temperature and humidity, etc.. A minimum of 30-60 minutes of dry time is recommended, with up to 4 hours preferred. It is recommended to wait at least 30 minutes after dry appearance before application of adhesive.

**Spread rate:** Coverage will vary with substrate porosity and condition. 300 Square feet per gallon is an average number with up to 800 square feet per gallon on previously sealed or non-porous surfaces.

**Shelf Life:** 12 months at room temperature in original unopened container.

**Viscosity:** ~ 25 - 35 sec @ 25 C - 6 mm DIN cup

**Weight / Gal:** 8.49 lb

**VOC content:** 39.8 g/L

**Clean up:** Water and/or glycol ether EB.

Always wear appropriate personal protective equipment (PPE) when working with chemicals. See SDS for more information.

This information is based on current experience and research and should be considered as recommendation only, without obligation or warranty of any kind. Final determination as to the suitability of this product for any purpose or process is the responsibility of the user, and should only be made after proper and careful testing of the complete coating system. For further information see SDS or contact Trustor Coatings at 715 849-2989. Issued August 2023.