



Max Wall-Mounted HEE

Indoor Unit AC100BNTPKG/EU Outdoor Unit - Mono-Phase AC100BXAPKG/EU Outdoor Unit - Tri-Phase AC100BXAPNG/EU

Indoor Unit AC100BNTPKG/EU Outdoor Unit - Mono-Phase AC100BXAPKG/EU Outdoor Unit - Tri-Phase AC100BXAPNG/EU

SI	NMSUNG	
5/	AMSUNG	DIGITAL INVERTER

Specifications

Max Wall-Mounted HEE (R32)



- Full HD Filter.
 Wi-Fi kit (optional)
 Operation range from -25°C until 52°C
 100% heating capacity at -15°C
 Base heater as standard
 Inverter PBA self-diagnosis

Indoor Unit Outdoor Unit - Mono-Phase			AC100BNTPKG/EU AC100BXAPKG/EU	
Capacity				
	Cooling (Min/Nominal/Max)	kW	3.60 / 9.50 / 12.10	
	Heating @ +7 °C (Min/Nominal/Max)	kW	2.90 / 10.80 / 16.20	
	Heating @ -5 °C	kW		
	Heating @ -15 °C	kW		
Performance				
Energy Efficiency Cooling	SEER ¹	W/W	6.9/ A++	
	Power Consumption	kWh/a	482	
	Pdesignc	kW	9.5	
	EER	W/W	3.47	
Energy Efficiency Heating	SCOP ¹	W/W	4.1/ A*	
	Power Consumption	kWh/a	2220	
	Pdesignh (average)	kW	6.5	
	COP ¹	W/W	3.13	
Airflow Rate	Indoor Unit (H/M/L)	m³/min	22.7/19.8/17.8	
Sound Power	Indoor Unit	dB(A)	65	
	Outdoor Unit	dB(A)	66	
Sound Pressure	Indoor Unit (H/M/L/Silent)	dB(A)	49/46/43/37	
	Outdoor Unit (H/L)	dB(A)	54/52	
Fan/Outdoor Unit	Туре		BLDC	
	Power	W	125	
	Number of Fans	-	1	
Operating	Cooling	°C	-20~52	
Temperature Range	Heating	°C	-25.0~24.0	

	-	-	
\$AM\$ung		D some samely	
		10	

Indoor Unit Outdoor Unit - Mono-Phase			AC100BNTPKG/EU AC100BXAPKG/EU	
Electrical Data				
Power Source	Indoor Unit	Φ, #, V, Hz	1Ф, 2, 220~240 V, 50 Hz	
	Outdoor Unit Mono-Phase	Φ, #, V, Hz	10, 2, 220~240 V, 50 Hz	
	Outdoor Unit Tri-Phase	Φ, #, V, Hz	3Φ, 4, 380~415 V, 50 Hz	
Compressor Type	Outdoor Unit	Туре	Twin BLDC Rotary	
Power	Cooling	kW	0.78 / 2.74 / 4.20	
(Min/Nominal/Max)	Heating	kW	0.65 / 3.45 / 6.40	
Current Input	Cooling (Min/Std/Max)	A	4.0 / 12.3 / 18.3	
	Heating (Min/Std/Max)	A	4.0 / 15.3 / 27.9	
	Cooling - Tri-Phase (Min/Std/Max)	А	1.5 / 4.6 / 6.7	
	Heating - Tri-Phase (Min/Std/Max)	Α	1.3 / 5.6 / 9.3	
Dimensions				
Net Dimensions (W x H x D)	Indoor Unit	mm	1,280 x 345 x 253	
	Outdoor Unit	mm	940 x 1,420 x 330	
Net Weight	Indoor Unit	kg	18.5	
	Outdoor Unit	kg	100	
Refrigerant				
Refrigerant	Туре		R32 (contains fluorinated greenhouse gases. GWP = 675)	
	Factory Charging	kg	3.5/30 m	
	Charging Ton equivalent CO ₂	tCO2e	2.36	
	Additional Refrigerant Charging	g/m		
Piping Connections	Liquid Pipe	ø, inch	3/8	
	Gas Pipe	ø, inch	5/8	
Piping Length	Min/Max	m	5/ 85	
Piping Height	Max	m	30	
Piping Connections	Drain Pipe	ø, mm	ID 18	



¹ Energy labels as shown are according to EU No 626/2011 (LOT10) label classification 2019, on a scale from D to A+++.

Dimensional drawings

Max Wall-Mounted HEE (R32)



SAMSUNG

Find your flow.

Create your perfect environment.

Learn more about Samsung Climate Solutions at: www.samsung.com/climate

Copyright © 2022 Samsung Electronics Air Conditioner Europe B.V. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co., Ltd. Specifications and designs are subject to change without notice and may include preliminary information. Non-metric weights and measurements are approximate. All data was deemed correct at the time of creation. Samsung is not liable for errors or omissions. Some images may be digitally altered. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognised and acknowledged.



msung Electronics Co., Ltd. participates in the Eurovent Certification Programme (ECP) for Air nditioners (AC), Variable Refrigerant Flow (VRF) and Liquid Chilling Packages Heat Pump (LCP-P) To check the oppoing validity of certification, please visit, www.eurovent-certification.com



Officiel dansk SAMSUNG distributør Thorndahlsvej 6 | 9200 Aalborg SV Tlf: 70 22 13 66 | Mail: info@wellair.dk www.wellair.dk