







— THE NATURAL FIBER WALLCOVERING —

The agave sisalana plant is native to Mexico's Yucatán Peninsula, where the early Mayan city of Coba prospered in trade. Noted for its tensile strength, sisal has been used predominately for baler twine and rope. Centuries later, sisal became a thriving export of Mexico.

Today, we offer Coba® wallcovering as an homage to the origin of sisal fibers. The sisal fibers are vat-dyed to color specification and woven to create a beautiful, long-lasting wallcovering. Coba wallcovering adds elegance and interest to any wall through its natural texture. Not only does sisal provide a design element, but its strength is for areas that see a lot of traffic. Sisal is economical to install and skillfully covers concrete block and other rough surface walls. With 12 colors to choose from, Coba is sure to transform any space.

COLORS









FEATURES



LEED

Coba® wallcovering is made from 100% sisal, which is a rapidly renewable product. Coupled with Fibreworks® proprietary, low-VOC adhesive, this product is perfect for anyone seeking LEED certification.



ULTIMATE PROTECTION

Coba provides incredible protection by weaving high tensile strength fibers into a solid covering that will not scratch or mar. It is ultimate protection that still provides a warm, natural aesthetic.



SOUND ABSORBENT

As a natural fiber, sisal has inherent acoustical properties which improves sound quality by reducing echo and creates an environment that is more enjoyable.



ANTI-STATIC

Sisal is naturally anti-static. Unlike many other wallcovering products, Coba does not create static electricity that is passed on to people giving them a nasty shock once discharged.



VERSATILE

Ideal for installation on a variety of substrates; concrete block, plaster, brick, and drywall. The versatility of Coba wallcovering offers solutions to a myriad of problems you might encounter.

SPECIFICATIONS

Composite & Construction: 100% sisal; Boucle weave

Pile Height: 1/4"

Weight: Minimum of 48 oz/sq yd

Type: Reversible weave without backing

Roll Dimensions: 12' x 100'; 13' x 50' subject to availability

Quality Assurance: Class A Flame Spread Rating; ASTM-E84; Passes

Corner Burn Test; UBC 8-2 & NFPA 265

Acoustical: NRC Value: .10 avg ASTM C: 423-90a

Static Control: 100% static free

Environmental: LEED credits available rating sys; (USGBC); Rapidly

renewable bio-based material; Low-emitting materials

Approved Adhesive: Fibreworks #257 Sisal Adhesive - instant tact, dries firm, non-hazardous, low moisture, latex & water soluble, VOC compliant

*Notice: Fibreworks #257 Sisal Adhesive is the only recommended adhesive. Fibreworks® will not guarantee Coba® wallcovering installation when another adhesive is used. If you have any questions, please call Fibreworks.



