



— THE NATURAL FIBER WALLCOVERING —

- Extremely durable
- Minimal wall preparation
- Sound absorbent
- Class A Flame Spread
- Biodegradable
- Ideal for high abuse areas
- Sisal transforms “institutional” appearances to a warm, natural look
- A Grown Green Product

**Compostive & Construction:** 100% Sisal, Boucle Weave

**Pile Height:** 1/4”

**Weight:** Minimum of 48 oz/sq yd

**Type:** Reversible weave without backing

**Roll Dimensions:** 12’ x 100’; 13’ x 50’ subject to availability

**Quality Assurance:** Class A Flame Spread Rating; ASTM-E84;  
Passes Corner Burn Test; UBC 8-2 & NFPA 265

**Acoustical:** NRC Value: .10 avg ASTM C: 423-90a

**Static Control:** 100% static free

**Environmental:** LEED Credits available rating sys; (USGBC);  
Rapidly renewable bio-based material; Low-emitting  
materials

**Approved Adhesive:** Fibreworks #257 Sisal Adhesive - instant  
tact, dries firm, non-hazardous, low moisture, latex & water  
soluble, VOC compliant

**Notice:** Fibreworks #257 Sisal Adhesive is the only recommended adhesive for Coba Wallcovering. Fibreworks will not guarantee any installation of sisal when another adhesive is used. If you have any questions, please call Fibreworks.