



— THE NATURAL FIBER WALLCOVERING —

- Extremely durable
- Minimal wall preparation
- Sound absorbent
- Class A Flame Spread
- Biodegradable
- Ideal for high abuse areas
- Sisal transforms “institutional” appearances to a warm, natural look
- A Grown Green Product

Compostive & Construction: 100% Sisal, Boucle Weave
Pile Height: 1/4”
Weight: Minimum of 48 oz/sq yd
Type: Reversible weave without backing
Roll Dimensions: 9’ x 100’; 12’ x 100’; 13’ x 50’ subject to availability
Quality Assurance: Class A Flame Spread Rating; ASTM-E84; Passes Corner Burn Test; UBC 8-2 & NFPA 265

Acoustical: NRC Value: .10 avg ASTM C: 423-90a
Static Control: 100% static free
Environmental: LEED Credits available rating sys; (USGBC); Rapidly renewable bio-based material; Low-emitting materials
Approved Adhesive: Fibreworks #257 Sisal Adhesive - instant tact, dries rm, non-hazardous, low moisture, latex & water soluble, VOC compliant

Notice: Fibreworks #257 Sisal Adhesive is the only recommended adhesive for Coba Wallcovering. Fibreworks will not guarantee any installation of sisal when another adhesive is used. If you have any questions, please call Fibreworks.



2301 Brennen Business Court Louisville, KY 40299
1-800-843-0063 press 3 | www.fibreworks.com