



Using the Sun to Build a Better Generator™

# 24V BACKUP

# BATTERY GENERATOR

A “one-person carry” lithium iron phosphate (LiFePO4) battery generator capable of running 24V loads and expanding SunKit and SunCase battery capacity



5120Wh of DC energy in a wheeled case with Anderson industrial connectors Bluetooth communication directly from the Battery Management System (BMS) provides accurate state of charge information and remote control capabilities

## BENEFITS

- ☑ Battery Case allows for rapid deployment in rugged environments
- ☑ Anderson connectors allow for easy and safe connection
- ☑ Avoid using an AC Battery Generator for DC loads
- ☑ Easy to use Bluetooth App
- ☑ Vs. comparable Lead Acid Battery
  - 60% of the weight
  - 20+ times longer cycle life
  - tolerates prolonged deep discharges
  - five times longer calendar life in float applicaitons
  - 2x the energy, even with a higher discharge rate
  - better tolerance of high temperatures
  - lower lifetime ownership cost
- ☑ Vs. comparable nickel manganese cobalt battery
  - higher thermal runaway point
  - lower risk of explosion or combustion due to dropping/hitting the battery, overcharging the battery or short circuiting it

## APPLICATIONS

- ☑ Adding additional battery capacity to NUE SunCases
- ☑ Temporary battery backup
- ☑ DC-Powered Lighting
- ☑ Any 24V DC Load



Using the Sun to Build a Better Generator™



P: +1 (844) 941-3476  
E: sales@newuseenergy.com  
W: newuseenergy.com  
A: 3320 W Flower St. Phoenix, AZ 85017

# Specifications

Backup Battery Version	24V 200Ah
Battery Type	Lithium Iron Phosphate (LiFePO4)
Storage Capacity	5.12 kWh
Estimated Cycle Life based on an 80% Depth of Discharge (subject to other variables including temperature and load)	6,000
DC Nominal Voltage	25.6 V
Operating Voltage Range	24-29V DC
Max Continuous Charge Current	150A
Nominal and Minimum Capacity	200Ah
Max Continuous Discharge Current	150A
Peak Discharge Current	160±5A 3-7S
Maximum in Parallel	4
Discharge Temperature Range	-4-140°F (-20-60°C)
Charging Temperature Range	32-131°F (0-55°C)
Weight	99lb (45kg)
Dimensions	23"x18"x11" (57x44x26cm)
Warranty and Certifications	5-YEAR LIMITED MANUFACTURER'S WARRANTY UN 38.3, UL (Cell), and CE (Cell)Certified.

