

## PVC FABRIC REINFORCED DUCTING



### CONSTRUCTION:

Double ply PVC coated polyester fabric with an encapsulated spring steel wire helix.

### COLOUR:

Black.

### STANDARD LENGTH:

10 Metres.

### TEMPERATURE RANGE:

-30°C to +100°C in a 20°C ambient.

### APPLICATIONS:

Extraction of air, dust, welding fumes and air conditioning.

### PROPERTIES:

Very flexible and easily compressed.

### OPTIONS:

Various colours  
Heavier wire  
Closer wire pitch.

### Technical Data

Diameter mm	Weight Kg/m	Bend Radius mm	Max. Work. Press. Bar	Max. Vacuum Bar
38	0.11	28	0.90	0.20
51	0.13	35	0.80	0.20
65	0.18	42	0.75	0.18
76	0.22	53	0.60	0.10
80	0.24	56	0.60	0.10
89	0.27	63	0.55	0.09
102	0.30	70	0.50	0.09
115	0.35	85	0.50	0.08
127	0.38	88	0.50	0.08
140	0.42	95	0.35	0.06
152	0.45	105	0.20	0.06
160	0.52	110	0.20	0.05
178	0.63	123	0.20	0.05
203	0.72	140	0.20	0.05
228	0.81	157	0.15	0.04
254	0.90	175	0.10	0.04
305	1.08	210	0.06	0.03
357	1.26	245	0.05	0.02
408	1.45	280	0.04	0.02
458	1.63	315	0.03	0.01
508	1.82	350	0.02	0.01

Technical data at + 20°C.

Other diameters/lengths available upon request.