

Fingertip Contact Transducers



The **Fingertip Contact Transducers** are rugged and built to withstand direct contact with a variety of materials. These transducers feature wear plates and wear rings to hold up to rigorous inspections.

These transducers are available from 2.25MHz – 10MHz in a wide variety of sizes.

SKU #	Description
FC-2-250-G	2.25 MHz, .25" Dia., Microdot
FC-2-250-H	2.25 MHz, .25" Dia., Microdot, HR
FC-2-375-G	2.25 MHz, .375" Dia., Microdot
FC-2-375-H	2.25 MHz, .375" Dia., Microdot, HR
FC-2-500-G	2.25 MHz, .5" Dia., Microdot
FC-2-500-H	2.25 MHz, .5" Dia., Microdot, HR
FC-2-750-G	2.25 MHz, .75" Dia., Microdot
FC-2-750-H	2.25 MHz, .75" Dia., Microdot, HR
FC-3-250-G	3.5 MHz, .25" Dia., Microdot
FC-3-250-H	3.5 MHz, .25" Dia., Microdot, HR

SKU #	Description
FC-3-375-G	3.5 MHz, .375" Dia., Microdot
FC-3-375-H	3.5 MHz, .375" Dia., Microdot, HR
FC-3-500-G	3.5 MHz, .5" Dia., Microdot
FC-3-500-H	3.5 MHz, .5" Dia., Microdot, HR
FC-5-250-G	5 MHz, .25" Dia., Microdot
FC-5-250-H	5 MHz, .25" Dia., Microdot, HR
FC-5-375-G	5 MHz, .375" Dia., Microdot
FC-5-375-H	5 MHz, .375" Dia., Microdot, HR
FC-5-500-G	5 MHz, .5" Dia., Microdot
FC-10-500-H	10 MHz, .5" Dia., Microdot, HR