

Apollo

F: .:. I. . . . /C . I

Series Apollo

Product

Chandelier - 6 Lights

Dimensions

L 53in/135cm x W 6in/15cm x H 41.5in / 105.4cm

Shipping Dimensions

L 63in/160cm x W 19in/48cm x H 15in/38cm

Weight

8.5lb/3.8kg

<u>Materials</u>

Brass, Aluminum, Glass, White Oak

Finishes/Colors

Matte black metal / Brushed brass detail, Matte ivory metal / Brushed brass detail

Chandelier - 6 Lights

<u>Suspension</u>

Two 1/2-inch diameter stems in matching metal finish. 35in length included. 72in length available for additional cost. Stems length can be adjusted on site.

Canopy

L 14in / 36cm x W 5in / 13cm x H 2in / 5cm solid white-oak. Available in 2 coordinating finishes: Oxidized oak for Matte black and Brushed brass metal fixtures, Whitewashed oak for Matte ivory metal fixtures.

Ceiling Slope

0°- 10° mounting slope. Up to 90° variable hang-straight available upon request.

Certifications UL/cUL (120V) CE (240V) 120V Illumination

Integrated LED Wattage: 30W

Lumens: 2,100 Lumens est.

Color Temperature: 2700 K, 90+ CRI LED Lifetime: 50,000 Hours est. Dimming: Triac and ELV

240V Illumination

Integrated LED Wattage: 30W

Lumens: 2,100 Lumens est.

Color Temperature: 2700 K, 90+ CRI LED Lifetime: 50,000 Hours est.

Dimming: ELV or 0-10V

Driver location

Driver located in the canopy

Fixture Mounting

Designed to be mounted on standard 4in.

Electrical Box.

Two #8-32 screws included.

Additional mounting hardware provided

for 240V versions.