

Apollo

Series Apollo

Product

Pendant - Corded

Dimensions

 $\phi 8 \text{in} / \phi 20 \text{cm} \times H 104.5 \text{in} / 264 \text{cm}$

Weight

3.3lb / 1.5kg

Shipping Dimensions

L 22in / 56cm x W 16in / 41cm x H 10in / 25cm

Shipping Weight

7lb / 3kg

Materials

Brass, Steel, Glass, White Oak

Pendant - Corded

Finishes/Colors

Brushed Brass detail / Oxidized oak Canopy

Suspension

Black cord 96in / 244cm length included. 144in / 366cm length available for additional cost. Cord length can be adjusted on site.

Canopy

 ϕ 5.5in / ϕ 14cm x H 2in / 5cm solid white-oak. Available in 2 coordinating finishes: Oxidized oak for Matte black and Brushed brass metal fixtures, Whitewashed oak for Matte ivory metal fixtures.

Ceiling Slope

0°-10° mounting slope. Up to 90° variable hang-straight available upon request.

Certifications **UL/cUL** (120V) CE (240V)

120V Illumination

Integrated LED Wattage: 10 W

Lumens: 800 Lumens est.

Color Temperature: 2700 K, 90+ CRI LED Lifetime: 50,000 Hours est. Dimming: Triac, ELV or 0-10V

240V Illumination

Integrated LED Wattage: 10 W

Lumens: 800 Lumens est.

Color Temperature: 2700 K, 90+ CRI LED Lifetime: 50,000 Hours est.

Dimming: ELV or 0-10V

Driver location

Driver located in the canopy

Fixture Mounting

Designed to be mounted on standard 4in.

Electrical Box.

Two #8-32 screws included.

Additional mounting hardware provided

for 240V versions.