



RTI-INF1 Infinity Router Plate/Triton Router Mounting Instructions

Things You Will Need:

1. RTI-INF1 Infinity Router Table Plate with included hardware
2. Triton router model TRA001 or model MOF001

Mounting the Router to the Plate

- Remove the factory plastic sub-base from the router and retain the 4 mounting screws. These screws will be used to attach the Infinity RTI-INF1 router plate to the router.
- Position the Infinity plate on the router with the screw holes in the plate and router base aligned. Be sure to locate the appropriate hole in the Infinity plate over the height adjustment notch in the router base. Use the 4 screws to secure the plate to the router's base.
- Install the 10 set screws into the corresponding holes around the perimeter of the plate. Install the assembly into the router table with the Infinity logo in the front right corner. Adjust the 3 cam disks on the underside of the plate to eliminate any side-to-side play between the plate and table opening.
- Adjust the leveling screws so that the plate sits flush with the router tabletop on all sides.
- (OPTIONAL): If using an Infinity router tabletop, install the 4 flathead screws into the corners of the plate and lightly tighten them to secure the plate and router in the tabletop. Over-tightening these screws can affect the level of the plate and cause damage to the table. The screws are intended only to secure the router so it does not move during use. A small amount of blue Loctite or other non-permanent thread-locking compound can be used to ensure the screws do not loosen during use.

310 Mears Blvd • Oldsmar, Florida 34677

P: 813-881-9090 | 1-877-872-2487 - Order Online 24/7: InfinityTools.com