

Triton's multi award-winning TRA001 is perfect for both table-mounted and hand-held use. One of its most significant features is the single-button switch from conventional plunge router to fixed-base mode router, and the 3-stage, pre-set height adjustment system allows the plunge return spring to be removed in just seconds for easy lifting and adjustment of the machine when mounted in a router table. For enhanced safety, the automatic spindle lock will only engage when the power switch safety cover is closed, ensuring the tool cannot accidentally be switched on during the bit change procedure.

**Soft Start & Variable Speed**

provides the perfect speed for all cutter types

**Micro Winder**

enables continuous fine depth adjustment through the full plunge range

**Quick Access Brushes**

allows the end user to change worn brushes



**Removable Plunge Spring**

for easy bit adjustment when table mounted

**Safety Switch Shutter**

locks closed in bit-change mode to prevent router being switched on

**Switching from a Plunge to a Fixed Based Router**

with rack & pinion adjustment is as simple as pushing a button

**Side Air Vents**

reduce intake of dust into the motor casing when mounted upside-down in a router table

**Fully Enclosed Guarding**

provides maximum protection from the cut zone & assists dust extraction

**1/2" & 1/4" (EU: 1/2" & 12mm) Collet**

for a greater range of bit shank sizes

**3-Stage Turret**

with direct reading scales for precise pre-set cut depths



**Bit Change**

through the base a single wrench bit change is achieved with the automatic spindle lock

## Key Features

- Powerful 3¼ HP (15A) electronically controlled motor
- Single switch from plunge to fixed-base router with rack & pinion height adjustment
- 8000-20000rpm electronic speed maintenance under load
- Automatic spindle lock for single wrench bit changes
- 3 stage turret with direct reading scales for precise pre-set cut depths
- Soft start & variable speed provides the perfect speed for all cutter types
- Micro winder enables continuous fine depth adjustment

## In the Box

- Table Height Winder
- Collet Wrench
- 1/2" & 1/4" Collet
- Manual
- Multi-Function Fence



Edge Guide

## Key Specifications

	Voltage
	110-120V 60Hz
Power	3¼HP / 15A (2100W)
Speed	8000 - 20000rpm
Collet	½" & ¼"
Plunge Range	0 - 2.6"
Extraction	Dust Extraction Port
Weight	13.2lbs / 6kg
MSRP	\$289.99