Conquer the outdoors and extend the riding season for all year fun.

ELECIRIC BIKES

26" x 4.8" eFATBIKE OUTLAND **TORNGAT RS**

ALL SEASON RIDING POWERHOUSE

Enhanced control and handling capability over sand, snow and through mud with a dynamic motor system delivering all the advantages of electric assist while maintaining a traditional riding experience.



POWER ON DEMAND THROTTLE



Configurable to **CLASS 1 CLASS 3** capable where permitted **

MOTOR & THROTTLE

130Nm/500W mid motor with Torque/Cadence sensing and throttle delivers a powerful and intuitive natural riding experience.

POWER AND RANGE

720Wh battery providing up to 60km (37mi)* range with 4.8" tires. Ready everyday with plug and play charging and all day range.

PEDAL ASSIST SEGMENTS

Eco/Tour/Sport/Turbo/Boost User programmable and seamless intelligent riding experience.



SITE NORMAN










OUTLAND TORNGAT RS

26" x 4.8" eFATBIKE


FRAME	Hydroformed Alloy, 26 Fatbike frame, internal cable routing head tube ported,				
COLOR FORK	removable down tube battery with security lock Red and Black RST RENEGADE 26* suspension, 120mm travel, lockout, Thru Axle				
DRIVETRAIN		COMPONENTS			
SHIFTERS CHAINRINGS CHAIN REAR DERAILLEUR CASSETTE	SHIMANO ALIVIO 9-speed Rapidfire Plus 34T with Narrow Wide teeth KMC E9-S SHIMANO ALIVIO 9-speed SHIMANO ALIVIO 9-speed 11-36T	HANDLEBAR GRIPS STEM SEAT POST SADDLE BRAKE LEVERS BRAKE CALIPERS	700mm, 28mm rise, 31.8mm dia. VELO, Rubber palm rest, 132mm 41mm with 3 degree rise, 31.8mm clamp dia. EXA KSP900-1 Dropper Post, 150mm travel (445mm) SELLE ROYAL Viento TEKTRO HDE350 with power cut off switch TEKTRO HDE350 Hydraulic Disc		
WHEELS TIRES	MAXXIS Minion M346(F) M347(R) 26"x4.8	ROTORS "	180mm		
RIMS	26"x95mm Fat bike rim				
ELECTRIC TECHNOLOGY					
BLUETOOTH DISPLAY UNIT MOTOR FORQUE	2" HD High Brightness IPS Color LCD Disp USB Charging Port, Light Auto On/Off Opti Main Power/PAS Control/Ride, Stats and S Battery Voltage/Capacity Percentage/Ran Diagnostic and Warning Information, Walk iGO DRIVE RS 500W mid motor, 48V up to 130Nm	lay, Ergonomically Designed Bu on (Ambient Light Detector), Ir Settings Toggle, PAS Level/Bati ge/Accumulated Charging Cyc Assist	les, Motor Power Output Average/Maximum, Ride Analysis Statistics,		
ELECTRIC TECHNOLOGY BLUETOOTH DISPLAY UNIT MOTOR TORQUE BATTERY RANGE PEDAL ASSIST SYSTEM	2" HD High Brightness IPS Color LCD Disp USB Charging Port, Light Auto On/Off Opti Main Power/PAS Control/Ride, Stats and S Battery Voltage/Capacity Percentage/Ran Diagnostic and Warning Information, Walk iGO DRIVE RS 500W mid motor, 48V	lay, Ergonomically Designed Bu on (Ambient Light Detector), Ir Settings Toggle, PAS Level/Batt ge/Accumulated Charging Cyc Assist security lock (48V 15Ah 720	uttons, IP65 Waterproof, Password Protected Power On Option, Iterface Color Coded Display Reference (for Quick Glance Safety), Iery/Power/Clock, Speedometer/Max Speed/Avg Speed, Trip Distance, Ies, Motor Power Output Average/Maximum, Ride Analysis Statistics,		

ACCESSORIES INCLUDED

Front LED light XC-259A (powered by main battery), Water Bottle Bosses on Seat Tube, Kickstand, VP-501 Alloy MTB Pedals - Black, Bell, Tool Kit, Battery Charger







FRAME SIZE	48.5cm (19.1")		
A SEAT TUBE LENGTH	485mm	H BOTTOM BRACKET HEIGHT	324mm
B SEAT TUBE ANGLE	73°	BOTTOM BRACKET DROP	59mm
C EFFECTIVE TOP TUBE LENGTH	622mm	J CHAINSTAY LENGTH	494mm
D STACK	681mm	CRANK LENGTH	170mm
E REACH	440mm	L WHEELBASE	1228mm
F HEAD TUBE LENGTH	150mm	M SADDLE HEIGHT (MIN/MAX)	89.5cm / 104.5cm (35.2" / 41.1")
G HEAD TUBE ANGLE	68.5°	N STAND OVER HEIGHT	78cm (30.7")



Bluetooth

USB

× :

CHARGING