

# Product Specifications / Technical Data



GENCORE™

Pattern #'s:	GEN-800, 801, 802, 803
Composition:	Phthalate-Free Polyvinyl Chloride
Installation Method:	Snap & Click
Size (inches / mm):	7.08" x 48.03" (179.8 x 1219.9mm)
Total Thickness:	5.0mm
Wear Layer:	20mil (.5mm)
Finish:	G55 MAX Advanced Coating System
Edge:	Painted Bevel
Sq.Ft. / Piece:	2.36
Sq.Ft. / Carton:	23.63
Pieces / Carton:	10
Cartons / Pallet:	50 (1181.50 sq.ft.)
Pallets / 20' Container:	20 (23,630 sq.ft.)
Weight / Pallet:	2,010lbs
Limited Warranty:	Lifetime Residential 10 Year Commercial

## Testing

ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 – Impact Sound Insulation Acoustical Testing (IIC)	54 IIC – over 6" concrete
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements

## Sustainability

Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes

[www.acrylusa.com](http://www.acrylusa.com)

1-855 3 RASKIN