

Product Specifications / Technical Data



Collection Name: Brooklyn Reserve- Bushwick

Composition:	Phthalate-Free Polyvinyl Chloride
Installation Method:	Snap & Click
Size (inches / mm):	7.15" x 48.62" (181.61 x 1234.9mm)
Total Thickness:	5.5mm
Wear Layer:	20mil (.5mm)
Finish:	G55 Advanced Coating System
Edge:	Bevel
Sq.Ft. / Piece:	2.41
Sq.Ft. / Carton:	24.11
Pieces / Carton:	10
Cartons / Pallet:	44 (1,060.84 sq.ft.)
Pallets / 20' Container:	20 (21,216.80 sq.ft.)
Weight / Pallet:	1658lbs
Limited Warranty:	Lifetime Residential 10 Year Commercial

Testing

ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 – Impact Sound Insulation Acoustical Testing (IIC)	51 IIC – over 6" concrete
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements

Sustainability

Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes

www.acrylxusa.com

1-855 3 RASKIN