

Product Specifications / Technical Data



Collection Name: Elevations - Interwoven

Effective: May 2, 2016

| | |
|--|--|
| Composition: | Vinyl – Gravity Backing – Phthalate Free |
| Size (inches / mm): | 19.68" x 39.37" (500 x 500mm) |
| Gauge: | 1/5" (5.0mm) |
| Wear Layer: | Woven |
| Finish: | G88 Advanced Coating System |
| Edge: | Square |
| Sq.Ft. / Piece: | 5.38 |
| Sq.Ft. / Carton: | 26.91 |
| Pieces / Carton: | 5 |
| Cartons / Pallet: | 36 (968.76 sq.ft.) |
| Pallets / 20' Container: | 20 (19,375 sq.ft.) |
| Weight / Carton: | 49lbs |
| Limited Warranty: | Lifetime Residential 10 Year Commercial |
| ASTM Testing | |
| ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread): | Meets and exceeds passing requirements (Class 1) |
| ASTM F925 – Resistance to Chemicals: | Meets and exceeds passing requirements |
| EN1814 – Fraying: | Meets and exceeds passing requirements |
| Slip Resistance: | Meets and exceeds passing requirements for ADA and OSHA Guidelines (>.6) |
| ASTM E492 - Impact Sound Insulation Acoustical Testing (IIC) | 57 IIC – Over 6" thick concrete slab with drop ceiling |
| ASTM E2192 – Impact Sound Insulation Acoustical Testing (Delta) | 18 IIC Delta – Over 6" thick concrete slab |
| ASTM F970 - Static Load Limit: | Meets and exceeds passing requirements (1,000 PSI-Modified) |
| Sustainability | |
| Recycled Content: | No |
| ISO 9001 – Quality Management System: | Meets and exceeds passing requirements |
| ISO 14001 – Environmental Management System: | Meets and exceeds passing requirements |
| FloorScore® Certified: | Yes |

www.raskinind.com

1-855 3 RASKIN