

# Product Specifications / Technical



## Collection Name: Elevations - Loft

Effective: May 1, 2023

Composition:	Phthalate-Free Virgin Vinyl
Size (inches / mm):	Plank: 7.08" x 47.24" (179.83 x 1199.89mm) Plank: 9.25" x 59.25" (234.9 x 1504.9mm) Tile: 12" x 24" (304.8 x 609.6mm) Tile: 23.6" x 23.6" (609.6mm x 609.6mm)
Gauge:	1/6" (4.0mm)
Wear Layer:	20mil (.5mm)
Finish:	G88 Advanced Coating System
Edge:	Micro-Bevel
Sq.Ft. / Piece:	Plank: 2.32-7.08" Plank: 3.80-9.25" Tile: 2 Tile: 3.87
Sq.Ft. / Carton:	Plank: 27.9-7.08" Plank: 30.46-9.25" Tile: 24 Tile: 31
Pieces / Carton:	Plank: 12-7.08" Plank: 8-9.25" Tile: 12 Tile: 8
Cartons / Pallet:	Plank: 45 (1,255.50 sq.ft.)-7.08" Plank: 64 (1,949.44 sq.ft.)-9.25" Tile: 48 (1,152 sq.ft.) Tile: 40
Limited Warranty:	Lifetime Residential 10 Year Commercial
<b>Testing</b>	
ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements

ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming)	Meets and exceeds passing requirements (Class 1)
Slip Resistance:	Meets and exceeds passing requirements for ADA and OSHA Guidelines (>.6)
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements
<b>Sustainability</b>	
Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management	Meets and exceeds passing requirements

[www.raskinind.com](http://www.raskinind.com)

1-855 3 RASKIN