

# Product Specifications / Technical Data



## Collection Name: Elevations – Tusk

Effective: September 30, 2016

Composition:	Vinyl – Gravity Grip
Size (inches / mm):	12" x 24" (304.8 x 609.6mm)
Gauge:	1/5" (5.0mm)
Wear Layer:	20mil (.5mm)
Finish:	G88 Advanced Coating System
Edge:	Square
Sq.Ft. / Piece:	2
Sq.Ft. / Carton:	20
Pieces / Carton:	10
Cartons / Pallet:	48 (960 sq.ft.)
Pallets / 20' Container:	20 (19,200 sq.ft.)
Weight / Carton:	35lbs
Limited Warranty:	Lifetime Residential 15 Year Commercial
<b>Testing</b>	
ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
Slip Resistance:	Meets and exceeds passing requirements for ADA and OSHA Guidelines (>.6)
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 - Impact Sound Insulation Acoustical Testing (IIC)	57 IIC – Over 6" thick concrete slab with drop ceiling
ASTM E2192 – Impact Sound Insulation Acoustical Testing (Delta)	18 IIC Delta – Over 6" thick concrete slab
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements (1,000 PSI-Modified)
<b>Sustainability</b>	
Recycled Content:	Yes
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes
Environmental Product Declaration, EPD® (SCS Global Services):	Verified

[www.raskinind.com](http://www.raskinind.com)

1-855 3 RASKIN